

# **PMI 2000**



Pramac PMi series inverter: optimal solution to combine silent operation with less fuel consumption and tension stability; the inverters Pramac stabilize the output tension and supply power for all kinds of equipment. They guarantee maximum efficiency: adjusting the speed according to the required load, our inverters reduce the average fuel consumption.

#### **FEATURES**

- Inverter technology: stable power for safe operation of sensitive electronics.
  OHV engine provides consistent power for multiple applications.
- · Low-oil level shutdown automatically safeguards engine from damage.
- Economy mode automatically adjusts the engine speed to the optimum level to provide excellent fuel economy and noise reduction.
- USB ports charges your mobile electronics so you can stay connected.Lightweight and compact.


- Easily transportable by handle.Ideal for applications requiring low noise.



PERFORMANCE		
Frequency	Hz	50
Voltage	V	230
Phase		1
Max Power	Watts	2000
Rated Power	Watts	1700



Engine		
Brand		Pramac
Туре		OHV
Exhaust emission level		Stage V
Operating Speed Nominal	rpm	Variable
Fuel		Petrol
Starting Systems		Recoil
Oil capacity	I	0.45
Low Oil Shutdown		$\checkmark$



# H

Inverter

535

305

460

22

555x310x480

(L) mm

(W) mm

(H) mm

Kg

mm

Autonomy		
Fuel tank capacity		3.5
Fuel consumption 50%	l/h	1.2
Running time 50%	h	3

Noise level		
Guaranteed noise level (LWA)	dB(A)	89
Noise pressure level @ 7 m	dB(A)	61

## GENSET CONTROL

#### COMMANDS

Alternator

Length

Width

Height

Dry weight

Voltage regulation system

Carton box dimension LxWxH

**Dimensional data** 

- Selector switch: O/I
- Air choke Valve
- Starting handle
- Smart throttle: Economy mode automatically adjusts the engine speed to the optimum level to provide excellent fuel economy and noise reduction.

#### INSTRUMENTATION:

- Voltmeter, Frequency meter, Wattmeter and Hourmeter (display)
- Outputting energy (indicator light Green)
- Overloading and Oil alarming (indicators light Red)
- PROTECTIONS
- Overload
- Oil Guard
- OUTPUT:
- DC12V 6A
- n°2 USB 5V 2A

## SOCKET TYPE

#### SCHUKO 230V 16A IP44

The information is aligned with the Data file at the time of download. Printed on 27/09/2021 (ID 10146)

©2021 | PR INDUSTRIAL s.r.l. | All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice







