

MG 5000 I-BE 5,3 LT



3000 rpm engine



Frontal panel



5,3 Lt Fuel Tank



Stage V

We offer now what others will do tomorrow.



GenSet s.p.a.

Via Stazione 5 - 27030
Villanova d'Ardenghi (PV) - Italy
Phone: +39-0382-5091

commerciale@genset.it
www.genset.it

GenSet
Next Gen technology
for top business.

PORTABLE SINGLE-PHASE POWER GENERATOR
OUTPUT POWER 5 kVA
PETROL ENGINE 3000 RPM
5,3 LT FUEL TANK

Standard Features	<ul style="list-style-type: none"> • Low oil level shutdown device • 2 x 230 V - 50 Hz single-phase Schuko socket protected by circuit breaker
Options available as factory options	<ul style="list-style-type: none"> • Versions with different voltages • 60Hz version • Automatic voltage regulator (AVR)
Accessories on request	<ul style="list-style-type: none"> • Trolley: two-wheels and handles
Noise level	<ul style="list-style-type: none"> • Lwa 98 (73 dB a 7 mt)
AC generator - 50Hz	<ul style="list-style-type: none"> • Type: synchronous • Single-phase max. power : 5 kVA - 230 V • Power Factor: $\cos \phi$ 0,8
Petrol Engine 3000 rpm	<ul style="list-style-type: none"> • Type: Briggs & Stratton XR1450 - 1 cyl. - 8,3 HP (6,1 kWm) - 306 cm³ • Cooling system: air • Starting system: recoil • Fuel tank capacity: 5,3 lt • Fuel consumption @ 75%: 2,5 lt/h
Other features	<ul style="list-style-type: none"> • Insulation Class: H • Ambient temperature: 40 °C (*) • Altitude: 1000 mt (*) • Mechanical Protection: IP 23 • Dimensions (L x W x H): 770 x 480 x 625 mm • Dry weight: 62 kg