EA 7/3 GH

PORTABLE THREE-PHASE POWER GENERATOR / OUTPUT POWER **7,5 KVA** THREE-PHASE AND **4 KVA** SINGLE-PHASE / PETROL ENGINE **3000 RPM**

Gen Set Features

- + Low oil level cut out device
- + 1 x 16A, 400 V 50 Hz three-phase EEC socket protected by circuit breaker
- + 1 x 16A, 230 V 50 Hz single-phase EEC socket protected by circuit breaker
- + Earth Leakage Circuit Breaker (ELCB)

Gen Set Options (available as factory options)

+ Not available

+ Lwa 97

Accessories on Request

+ Trolley: two-wheels and handles

Noise Level

AC Generator 50 Hz

- + Type synchronous
- + Three-phase power (max.) 7,5 kVA 400 V + Single-phase power (max.) 4 kVA - 230 V
- + Power Factor 0,8

Petrol Engine 3000 rpm + Type Honda GX 390 OHV - 1 cyl. - 13 HP (9,6 kWm) - 390 cm³

(72 dB at 7m)

- + Fuel petrol + Cooling system air
- + Starting system manual recoil + Fuel tank capacity 6,5 l + Fuel consumption @ 75% 2,9 l/h

Other Features

- + Insulation Class H + Mechanical Protection IP 23
- + Dimensions (L x W x H) 730 x 480 x 520 mm
- + Dry Weight 80 kg

EA 7/3 GH



