



32 480

LUMENS



LUMAPHORE® LED 400L – 230V

PRIMO



LUMAPHORE® LED 400L is the first LUMAPHORE® equipped with Leds modules. So powerful as the LUMAPHORE® CFL 640, thanks to Leds its luminous flow is constant whatever is the outside temperature. It ignites immediately to 100% of its power and is much lighter. It offers powerful illumination of 32000 Lumens with 345 Watts. It is the ideal solution for many industry sectors :

- Road marking companies
- Road surfacing companies
- Emergency services
- Civil Security services
- Ski stations
- Road and motorway maintenance services

Benefits:

- 2,400 m2 area of lighting with 345 W output
- Lightweight and robust (ABS and PMMA Choc)
- 100% Immediate lighting
- Resistant to adverse weather conditions
- Extremely versatile for many uses





LUMAPHORE® LED 400L – Technical Data

Electrical Specifications

No. Of LED modules	8
No. Of LEDs per module	88
Total Lighting Output	320 W
Power of electricity supply	345 W
Connecting cable 3x1.5 ² head	10 m
Average life of LEDs	50000 hrs
Immediate illumination	yes

Safety Specifications

Protection index	IP44
Wind resistance	NC
Mast with guy wires	Yes
Temperature range for use	-15°/+40°

Photometric Specifications

Area of illumination	2400 m ²
Colour temperature	5000 °K
Lumens/module	4060
total Lumens	32480
Color rendering index	> 82

Mechanical Specifications

Diameter	22,5 cm
Length	91 cm
Weight	6 Kg
Optimal height for use	3 m
Average assembly time	2 mn



Honda Generator EU10i – 1000 W



Flight case



PMMA colored tubes

Accessories Available

Telescopic mast with or without winch
Carry Bag
Suspension cradle
Support with 15° angle
Switch 180/360 and/or ON/OFF
1000 W Generator
PMMA Coloured tubes

