




MOTOINVERTER 174 CE HONDA



Overview

MOTOINVERTER 174 CE HONDA

cod. 815791

Inverter technology, petrol engine-driven (HONDA engine) welding machine with high frequency permanent magnets alternator for electrode MMA and TIG-DC welding with scratch striking.

Use with a wide range of electrodes: rutile, basic, cellulosic, stainless steel, cast iron, etc.

It can also be used as direct current (DC) generator for powering electrical tools such as drills, sanders, etc.

Features:

- 4-stroke, air cooled petrol engine with recoil starter
- shutdown for lack of oil-over
- fast engine safeguard
- continuous welding current adjustment
- high current stability by variations in engine revs
- arc-force, hot start, anti-stick devices
- welding machine-generator selector switch
- thermostatic protection.

Technical data

CODE	CODE 815791	V_{DC}	DC AVAILABLE VOLTAGE 230 V		TANK CAPACITY 3,6 l
A_{MIN} / A_{MAX}	CURRENT RANGE 5 - 160 A	P_{DC}	DC AVAILABLE POWER 1,8 KW		FUEL CONSUMPTION 313 g/kWh
A_{MAX} 40°C	MAX CURRENT 130 A - 30 %	TYPE	TYPE HONDA GX200		NOISE LEVEL 97 LWA dB
A_{60%} 40°C	CURRENT AT 60% 90 A	P	POWER 4,8/6,5 kW/Hp		DIMENSIONS 75 - 37 - 43 cm
V₀	MAX NO LOAD VOLTAGE 110 V	Cc	DISPLACEMENT 196 cm ³		WEIGHT 40 kg



MOTOINVERTER 174 CE HONDA



D. USABLE ELECTRODES IN DC 1,6 - 3,2(4) mm



NUMBER OF REVS 3200 rpm



EAN CODE 800489774091 1



PROTECTION DEGREE IP23



STARTING RECOIL