

PMI 1000



Pramac PMi series inverter: optimal solution to combine silent operation with less fuel consumption and tension stability; the inverters Pramac stabilize the output tension and supply power for all kinds of equipment. They guarantee maximum efficiency: adjusting the speed according to the required load, our inverters reduce the average fuel consumption.

FEATURES

- Inverter technology: stable power for safe operation of sensitive electronics.
 OHV engine provides consistent power for multiple applications.
- Low-oil level shutdown automatically safeguards engine from damage.
- Economy mode automatically adjusts the engine speed to the optimum level to provide excellent fuel economy and noise reduction.
- USB ports charges your mobile electronics so you can stay connected.
 Lightweight and compact.


- Easily transportable by handle.
 Ideal for applications requiring low noise.



| PERFORMANCE | | |
|-------------|-------|------|
| Frequency | Hz | 50 |
| Voltage | V | 230 |
| Phase | | 1 |
| Max Power | Watts | 1000 |
| Rated Power | Watts | 850 |
| | | |



| Pramac |
|----------|
| OHV |
| Stage V |
| Variable |
| Petrol |
| Recoil |
| 0.25 |
| V |
| |



| Alternator | |
|---------------------------|----------|
| Voltage regulation system | Inverter |

| Dimensional data | | |
|----------------------------|--------|-------------|
| Length | (L) mm | 480 |
| Width | (W) mm | 250 |
| Height | (H) mm | 395 |
| Dry weight | Kg | 14 |
| Carton box dimension LxWxH | mm | 510x310x460 |



| Autonomy | | |
|----------------------|-----|------|
| Fuel tank capacity | | 2.1 |
| Fuel consumption 50% | l/h | 0.66 |
| Running time 50% | h | 3.2 |



| Noise level | | |
|------------------------------|-------|----|
| Guaranteed noise level (LWA) | dB(A) | 89 |
| Noise pressure level @ 7 m | dB(A) | 61 |

GENSET CONTROL

COMMANDS

- Selector switch: O/I
- Air choke Valve
- Starting handle
- Smart throttle: Economy mode automatically adjusts the engine speed to the optimum level to provide excellent fuel economy and noise reduction.

STATUS INDICATORS:

- Outputting energy (indicator light Green)Overloading (indicators light Red)
- Oil alarming (indicators light Red)

PROTECTIONS

- Overload
- Oil Guard

OUTPUT:

- DC12V 6A
- n°2 USB 5V 2A

SOCKET TYPE

| SCHUKO 230V 16A IP44 | 1 |
|----------------------|---|
|----------------------|---|



The information is aligned with the Data file at the time of download. Printed on 27/09/2021 (ID 10493)

