



GEN SET S.p.a.

Via Stazione,5 - 27030 Villanova D'Ardenghi (Pavia) Italy Tel. (+39) 0382-5091 - Fax (+39) 0382-509-244 E-mail: genset@genset.it - internet: //www.genset.it



MG 5/4 I-HE

PORTABLE THREE-PHASE POWER GENERATOR / OUTPUT POWER 5.5 KVA THREE-PHASE AND 2 KVA SINGLE-PHASE / PETROL ENGINE 3000 RPM

Gen Set Features

- + Low oil level cut out device
- + 1 x 16 A, 400 V 50 Hz three-phase EEC socket protected by circuit breaker + 1 x 16 A, 230 V 50 Hz single-phase EEC socket protected by circuit breaker
- + Earth Leakage Circuit Breaker (ELCB)

Gen Set Options

(available as factory options)

- + Versions with different voltages
- + 60 Hz version

Accessories on Request

+ Trolley: two-wheels and handles

Noise Level

+ Lwa 95

(70 dB a 7 m)

AC Generator 50 Hz

- + Type: synchronous
- + Three-phase power (max.): 5,5 kVA 400 V
- + Single-phase power (max.): 2 kVA 230 V
- + Power Factor: cos φ 0,8

Petrol Engine 3000 rpm

- + Type: Honda GX 270 OHV 1 cyl. 9 HP (6,6 kWm) 270 cm³
- + Fuel: petrol
- + Cooling system: air
- + Starting system: manual recoil
- + Fuel tank capacity: 61
- + Fuel consumption @ 75%: 2,2 l/h

Other Features

- + Insulation Class: H
- + Ambient temperature: 40 °C
- + Altitude: 1000 mt
- + Mechanical Protection: IP 23
- + Dimensions (L x W x H): 730 x 480 x 520 mm
- + Dry weight: 80 kg

Generator set in designed to operate in ambient temperature up to 40 °C and 1000 mt altitude - For higher values of temperature and altitude please consult factory to check available power.