

GS/B 20S4 1150X525 LOW PROFILE

EASY TO MOVE



LIFTER GS PRO, SPECIAL AND 3000 KG

The GS PRO pallet truck is equipped as a standard with an entry and exit roller and a more ergonomic handle than the GS Basic. Available with weight capacity of up to 3000kg.



MAXIMUM PRESSURE VALVE

When the maximum load capacity is exceeded, oil pressure exceeds its maximum limit and the valve automatically locks the forks. Thus possible structural damage is avoided.



VARNISHING

Following an appropriate conditioning operation the frame is varnished with polyester powder at a temperature of 250° to guarantee maximum resistance to wear and atmospheric agents.



Description			
1.1 Manufacturer			LIFTER
1.3 Drive			Manual
1.4 Operator type		, i	Pedestrian
1.5 Load capacity	Q	Kg	2000
1.6 Load centre distance	С	mm	600
1.8 Load axle to end forks	Х	mm	945
1.9 Wheel base	У	mm	1192

Weights		
2.1 Service weight	Kg	71
2.2 Axle load, laden rear	Kg	1378
2.2 Axle load, laden front	Kg	693
2.3 Axle load, unladen front	Kg	48
2.3 Axle load, unladen rear	Kg	23

Tyres/Chassis		
3.1 Tyres: front wheels		POLY.I./ NYLON
3.1 Tyres: rear wheels		STEEL
3.2 Tyre size: Steering wheels - Diameter	mm	200
3.2 Tyre size: Steering wheels - Width	mm	55
3.3 Tyre size: Load rollers - Diameter	mm	55
3.3 Tyre size: Load rollers - Width	mm	58
3.5 Tyre size: rear wheels - Q.ty (X=driven)	nr	4
3.5 Rear balancing axle		No
3.6 Tread, front	b10 mm	125
3.7 Tread, rear	b11 mm	365

Dimensions			
4.4 Lift height	h3	mm	115
4.9 Height of tiller in drive position max	h14	mm	1160
4.15 Height, lowered	h13	mm	56.5
4.19 Overall lenght	I1	mm	1550
4.20 Lenght to face of forks	12	mm	400
4.21 Overall width	b1	mm	525
4.22 Fork dimensions - Thickness	s	mm	40
4.22 Fork dimensions - Width	е	mm	160
4.22 Fork dimensions - Lenght	I	mm	1150
4.25 Distance between fork arms	b5	mm	525
4.32 Ground clearance, centre of wheelbase	m2	mm	15
4.34 Aisle width	Ast	mm	1822
4.35 Turning radius	Wa	mm	1367

Performance data		
5.2 Lifting speed laden	strokes	13
5.2 Lifting speed unladen	strokes	13

 $^\star\text{Available}$ accessories: tandem rollers, polyurethane rollers (as a standard on Premium), rubber guide wheels, manual control brake







