# Key features



### Swing handle



### Side discs



## Gearbox

### **SHOW SPECIFICATIONS**

### Function

| Max tilling width (mm)            | 800     |
|-----------------------------------|---------|
| Max tilling depth (mm)            | 325     |
| Forward speeds                    | 1       |
| Reverse speeds                    | 1       |
| Forward tool rotation speed (rpm) | 108 rpm |
| Reverse tool rotation speed (rpm) | 53rpm   |

#### **Dimensions**

| Dimension (L x W x H) (mm) | 1,500 x 837 x 980 |
|----------------------------|-------------------|
| Dry weight (kg)            | 53                |

### ACC

| Rotors/tines supplied | 6 x 4 tooth digging tines |
|-----------------------|---------------------------|
| Wheels                | Front Transport           |
| Side discs            | Yes                       |

### Engine

| Engine                                   | 4-stroke OHV          |
|--|-----------------------|
| Engine model                             | GP160                 |
| Engine displacement (cc)                 | 163                   |
| Engine net power (kW/rpm)                | 3.4/3,600             |
| Engine net torque (Nm/rpm)               | 10.3 / 2,500          |
| Fuel tank capacity (Litres)              | 2.4                   |
| Engine oil capacity (Litres)             | 0.58                  |
| Starter                                  | Recoil                |
| Drive clutch                             | Manual - belt tension |
| Transmission                             | Constant mesh         |
| Final transmission                       | Chain                 |
| Sound pressure at operators ears (dB(A)) | 84                    |
| Guaranteed sound power level (dB(A))     | 96                    |
| Vibration (m/sec²)                       | 7                     |

### Handle

| Height adjustable handle | Yes |
|--------------------------|-----|
| Swing handle             | Yes |