

# GENERATORS / ACDE 7000T



The three-phase ACDE 7000T generator for worksites is equipped with a diesel engine, THD (total harmonic distortion) value less than 6% and voltage accuracy between +6% and -6%.

The starting capability is 4 times the rated current.

### Connection

three-phase 380 V = N.1 CE socket, 16A three-phase 3P+N+E for full power

single-phase 220 V = N.1 CE socket, 16A single-phase 2P+E maximum for 50% of the generator power

12 V DC = N.2 screw type banana plugs one red (+) and one black (-)

## Protections

three-phase = three-pole switch (optional: four pole differential magneto-thermal switch)

# **12 V DC** = 10A fast fuse

Reading instrument

Electronic LED voltmeter for reading voltage

## **Recommended use**

Powerful electrical equipment, appliances, floodlights and lighting even if sensitive to voltage variations between no load and full load.

### Added value

The unit will not be damaged by an overload because the engine rpm lowers and the voltage drops to values under the operating limit, thereby preserving the unit and user. Once the load has been verified as excessive, it needs to be reduced, without stressing the user in overload.

GENERATOR	ACDE 7000T
Maximum power (kVA three/single)	7.0 (400V) 3.5 (230V)
Continuous power (kVA three/single)	6.5 (400V) 3.0 (230V)
Voltage (Volts)	400 / 230
Frequency (Hz)	50
DC output power (V/A)	No
Tank capacity (L)	5.5
Running time (h)	3.2
Noise level (dBA at 7m)	78
Battery	Yes
Wheel kit	Optional
Dry weight (Kg)	97
Dimensions (mm)	880x600x840
ENGINE	
Model	AMDE 186
Displacement (cc)	406
Power (Hp) at 3600 rpm	10
Туре	Diesel
Number of revolutions (rpm)	3000
Starting	Electric / Manual
Cooling	Air
Fuel	Diesel
ELECTRICAL COMPONENTS	
Type of voltage regulator	Compound
Protection rating	IP23
Thermal switch	Yes
Two/ four pole residual-current device	No
Oil alarm device	No
Voltmeter	Yes
Fuel level warning light	No
ATS control panel	No







http://www.axo-group.com/en/products/generators/acde-7000t.php

AXO GROUP SRL - Via Spallanzani, 15 - 42024 Castelnovo di Sotto (RE) Partita IVA, Codice Fiscale IT 02342860356 - Tel: 0522 688175 Fax: 0522 483731