

GENERATING SET

GE 3200 SX

FEATURES

- Engine shut down for low oil level
- Sockets: 1x230V 16A 2P+T CEE - 1x230V 16A 2P+T Schuko
- ELCB-GFI (Ground Fault Interruptor)
- Overload thermal shut off
- Protective frame
- Silenced
- Portable
- Meets EC Directives for safety and noise level



The images are for reference

Standard Equipment 										
	Petrol engine	Air cooling	Manual recoil	Engine shut down (oil)						
	Synchronous alternator	Sockets	ELCB-GFI	Thermal shut off	Battery charger					

Options on request

- Earthing kit

Technical data

GE 3200 SX

A.C. GENERATION - 50 Hz - *Single-Phase synchronous alternator, self-excited, self-regulated, brushless*

* **Stand-by single-phase power** 3.1 kVA (2.8 kW)/ 230 V / 13.5 A

* **PRP single-phase power** 2.8 kVA (2.5 kW)/ 230 V / 12.2 A

Cos φ 0.9

Battery charger 12Vc.c. - 10A

Insulation class H

* Output powers according to ISO 8528-1

ENGINE - *4-stroke petrol, OHV, Air cooling*

Model Honda GX 200

* **Stand-By net power** 3.7 kW (5.0 HP)

* **PRP net power** 3.3 kW (4.5 HP)

Cylinders/ Displacement 1/ 196 cm³

Speed 3000 rpm

Fuel consumption (75% of PRP) 1.1 l/h

* Powers according to SAE J1349

GENERAL SPECIFICATIONS

Tank capacity 3.1 l

Running time (75% of PRP) 2.8 h

IP protection degree IP 23

Dimensions LxLxh (mm) 570x420x450 mm

Dry weight 52 kg

* **Measured acoustic power LwA (pressure LpA)** 96 dB(A)(71 dB(A) @ 7m)

* **Guaranteed acoustic power LwA (pressure LpA)** 96 dB(A)(71 dB(A) @ 7m)

* Acoustic power according to European Directive 2000/14/EC