MOSA ISO 9001:2008 - Cert. 0192

GENERATING SET
GE 7554 HBS

FEATURES

- Engine shut down for low oil level
- Automatic voltage regulator AVR
- Sockets :1x400V 16A 3P+N+T CEE IP67
  2x230V 16A 2P+T SCHUKO
- Isometer
- Circuit breaker
- Protective frame
- Meets EC Directives for safety and noise level



IP54

The images are for reference

Standard Equipment										
Petrol engine	Air cooling	Manual recoil	Engine shut down (oil)	Hours-meter						
GS Synchronous alternator	AVR Automatic voltage regulator	3~ Sockets	1~ Sockets	R< Isometer	MT Circuit breaker	T Thermal shut off	V Voltmeter			

Options on request
- Earthing kit
- Exhaust extension
- Trolley CTM200
- Hand trolley TRM-7554 (4 foldable handles)

Technical data	GE 7554 HBS
A.C. GENERATION - 50 Hz - *Three-phase synchronous alternator, self-excited, self-regulated, brushless*	
*Stand-by three-phase power	7.5 kVA (6 kW) / 400V / 10.8A
*PRP three-phase power	6.5 kVA (5,2 kW) / 400V / 9.4A
*PRP single-phase power	5 kVA / 230V / 21.7A
Cos φ	0.8
Insulation class	H

* Output powers according to ISO 8528-1

ENGINE - *4-stroke petrol, OHV, Air cooling*	
Model	HONDA GX 390
* Stand-By net power	8.2 kW (11.1 HP)
* PRP net power	6.4 kW (8.7 HP)
Cylinders/ Displacement	1 / 389 cm³
Speed	3000 rpm
Fuel consumption (75% of PRP)	2.4 l/h

* Powers according to ISO 3046-1

GENERAL SPECIFICATIONS	
Tank capacity	6.1 l
Running time (75% of PRP)	2.5 h
IP protection degree	IP 54
* Dimensions Lxlxh	910x525x613 mm
* Dry weight	105 kg
** Measured acoustic power LwA (pressure LpA)	97 dB(A) (72 dB(A) @ 7m)
** Guaranteed acoustic power LwA (pressure LpA)	97 dB(A) (72 dB(A) @ 7m)

* Dimensions and weight without trolley/trailer / **Acoustic power according to European Directive 2000/14/EC

Mosa reserves the right to change this specification without notice. For further information please contact the sales department.

© MOSA - Viale Europa, 59 - 20090 Cusago (Milano) - Italy -phone +39-0290352.1 - fax + 39-0290390466 E-mail: info@mosa.it Web site: www.mosa.it