

GENERATING SET GE 7554 HBS-L

FEATURES

- Engine shut down for low oil level
- Automatic voltage regulator "AVR"
- Sockets : 1x400V 16A 3P+N+T CEE IP67
2x230V 16A 2P+T SCHUKO
- Isometer
- Circuit breaker
- Protective frame
- Meets EC Directives for safety and noise level



The images are for reference

Standard Equipment											
Options on request	• Earthing kit • Exhaust extension				• Trolley CTM10						

Technical data

GE 7554 HBS-L

A.C. GENERATION - 50 Hz - Three-phase synchronous alternator, self-excited, self-regulated

* Stand-by three-phase power	7,5 kVA (6 kW) / 400V / 10,8A
* PRP three-phase power	6,5 kVA (5.2 kW) / 400V / 9.4A
* PRP single-phase power	5 kVA/ 230 V / 21.7 A
Cos φ	0.8
Insulation class	H

* Output powers according to ISO 8528-1

ENGINE - 4-stroke diesel, direct injection, Air cooling

Model	Honda GX 390
* Stand-By net power	8.2 kW (11.1 HP)
* PRP net power	6.4 kW (8.7 HP)
Cylinders/ Displacement	1/ 389 cm ³
Speed	3000 rpm
Fuel consumption (75% of PRP)	2.4 l/h

* Powers according to SAE J1349

GENERAL SPECIFICATIONS

Tank capacity	18 l
Running time (75% of PRP)	7.5 h
IP protection degree	IP 54
*Dimensions LxIxh	935x525x645
*Dry weight	135 kg
**Measured acoustic power LwA (pressure LpA)	97 dB(A)(72 dB(A) @ 7m)
**Guaranteed acoustic power LwA (pressure LpA)	97 dB(A)(72 dB(A) @ 7m)

* Dimensions and weight without trolley/trailer. / **Acoustic power according to European Directive 2000/14/EC