



TECHNOLOGY 236 HD 230V ACX+ALU C.CASE



Overview

TECHNOLOGY 236 HD 230V ACX+ALU C.CASE

cod. 816207

MMA and TIG inverter electrode welding machine, in direct current (DC) with scratch striking.

Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron, etc.

Characteristics:

- compact and light
- high welding current stability in spite of mains voltage fluctuations
- regulation of arc force and hot start according to the type of electrode in use
- anti-stick device
- thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 15%) protections.

Complete with MMA welding accessories and aluminium carry case.

Technical data

CODE	CODE 816207	A_{MAX}	MAX ABSORBED CURRENT 42 A	Ø_{bc} MIN/MAX	D. USABLE ELECTRODES IN DC 1,6 - 4 mm
V_{1PH}	SINGLE PHASE MAINS VOLTAGE 230 V	A_{60% MAX}	ABSORBED CURRENT AT 60% - MAX 24 A	IP	PROTECTION DEGREE IP23
F	MAINS FREQUENCY 50 / 60 Hz	P_{MAX}	MAX ABSORBED POWER 6,6 kW	W_H L	DIMENSIONS 35,5 - 46,5 - 18,5 cm
A_{MIN} A_{MAX}	CURRENT RANGE 5 - 200 A	P_{60%}	ABSORBED POWER AT 60% 4,2 kW	kg	WEIGHT 9,8 kg
A_{MAX} 40°C	MAX CURRENT 200 A - 35 %	P_{GEN}	MOTORGENERATOR MINIMUM POWER 10 kW	BAR CODE	EAN CODE 800489781005 8
A_{60% 40°C}	CURRENT AT 60% 140 A	η	EFFICIENCY 84 %	Grid icon	PIECES/PALLET 30 pz/pallet



TECHNOLOGY 236 HD 230V ACX+ALU C.CASE



MAX NO LOAD VOLTAGE 81 V



POWER FACTOR (cosphi) 0,8

Included Accessories



DALLAS 300 ELECTRODE HOLDER 300A - 712260



TOLEDO 300 WORK CLAMP - 712231