

GREEN POWER GP610A-P-N OPEN

Reference: 01164



The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

You can choose between the versions:

- Open group with AVR-Leroy alternator (automatic power pack)
- Open group with AVR-Mecc Alte alternator (automatic power pack)
- Open group with AVR-Stamford alternator (automatic power pack)

The image is purely indicative.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	484
Continuous power three phase (KW)	440
Maximum power three phase (KVA)	605
Continuous power three phase (KVA)	550
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	1506A-E88TAG2
Emissions Regulations	NON EMISSIONATO

Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Elettrico
Engine capacity (cm ³)	8800
Number cylinders	6
Cylinders' position	In line
Cooling	Water
Alternator	MECC ALTE ECO40-1L/4
Poles	4
Protection degree	IP23
Fuel tank capacity (L)	320
Consumption (L/h)	90 Lt/h al 75% del carico
Running time (h)	3.54 h al 75% del carico
Length (mm)	3400
Width (mm)	1400
Height (mm)	2200
Dry weight (Kg)	4000
Silenced	No
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	AVR