



## GREEN POWER GP900A-P OPEN GENSET

Reference: 01172 AVR-Mecc alte automatica

### GREEN POWER GP900A-P OPEN GENSET

GREEN POWER GP900A-P OPEN is a three-phase genset with a rated of 900 kVA. It is powered by a Perkins 4006-23TAG3A engine. The genset is equipped with a MECC ALTE ECO43-2S alternator with a voltage of 400 V and a frequency of 50 Hz.

GREEN GP900A-P OPEN is designed for use in commercial and industrial applications, such as construction sites, factories and hospitals. It is ideal for providing emergency in the event of a blackout or for powering industrial machinery.

The GREEN POWER GP900A-P OPEN is a robust and reliable product that offers a number of advantages, including:

Versatility: the GREEN POWER GP900A-P genset can be used in a variety of applications.

Reliability: the GREEN POWER GP900A-P genset is robust and durable.

Efficiency: the genset has low consumption.

Safety: GREEN POWER GP900A-P genset is equipped with advanced safety systems.

#### Technical characteristics GENSET GREEN GP900A-P:

Maximum three-phase: 900 KV  
Maximum three-phase: 720 KW  
Fuel: Diesel  
Voltage: 230/400 V  
Engine: Perkins 4006-23TAG3A  
Starter: Electric  
Length: 4000 mm  
Width: 1800 mm  
Height: 2350 mm  
Weight: 6500 Kg

#### You can choose between the versions:

- Open group with AVR-Leroy alternator (automatic power pack)
- Open group with AVR-Mecc Alte alternator (automatic power pack)
- Open group with AVR-Stamford alternator (automatic power pack)

GREEN GP900A-P OPEN is a robust and reliable product that offers a number of advantages, including:

Versatility: it can be used in a variety of applications.

Reliability: it is robust and durable.

Efficiency: low consumption.

Safety: it is equipped with advanced safety systems.

If you are looking for a similar product GREEN GP900A-P or with similar features click [HERE](#).

Images purely indicative.

## Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	720
Continuous power three phase (KW)	640
Maximum power three phase (KVA)	900
Continuous power three phase (KVA)	800
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	Perkins 4006-23TAG3A
Emissions Regulations	NON EMISSIONATO
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Elettrico
Engine capacity (cm <sup>3</sup> )	22921
Number cylinders	6
Cylinders' position	In line
Cooling	Water
Alternator	LINZ PRO 22SD/4 - Sincrono
Poles	4
Protection degree	IP23
Fuel tank capacity (L)	400
Consumption (L/h)	130 Lt/h al 75% del carico
Running time (h)	3.07 h al 75% del carico

---

Length (mm)	4000
Width (mm)	1800
Height (mm)	2350
Dry weight (Kg)	6050
Silenced	No
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	AVR

---