



GREEN POWER GP505S/I-N SOUNDPROOF (MANUAL CONTROL UNIT)

Reference: 00780

The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	396
Continuous power three phase (KW)	360
Maximum power three phase (KVA)	495
Continuous power three phase (KVA)	450
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	FPT C13 TE6W
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm ³)	12800
Number cylinders	6
Cylinders' position	In line

Cooling	Water
Alternator	MECC ALTEECO40-2S/4
Poles	4
Fuel tank capacity (L)	410
Consumption (L/h)	24.7 Lt/h al 75% del carico
Running time (h)	9.62 h al 75% del carico
Acoustic pressure	69 dB(A)
Length (mm)	3950
Width (mm)	1450
Height (mm)	2190
Dry weight (Kg)	3630
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR