



## GREEN POWER GP505A/DO-N OPEN (MANUAL CONTROL UNIT)

Reference: 01108 AVR-Mecc alte automatica

### GREEN POWER GP505A/DO-N OPEN (MANUAL CONTROL UNIT)

Introducing the GREEN POWER GP505A/DO-N, an open-design generator equipped with a manual control unit. This model is tailor-made for those who value direct control and hands-on operation. Combining power with user-centric design, the GP505A/DO-N ensures a seamless power supply while offering an intuitive interface for easy management. As with all GREEN POWER products, this unit is a testament to the brand's commitment to quality and innovation. The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

""

#### Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	400
Continuous power three phase (KW)	360
Maximum power three phase (KVA)	500
Continuous power three phase (KVA)	450
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	1506A-E88TAG2

Emissions Regulations	Non Emissionati
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Elettrico
Engine capacity (cm <sup>3</sup> )	14618
Number cylinders	8
Cylinders' position	In line
Cooling	Water
Alternator	MECC ALTEECO40-2S/4
Poles	4
Fuel tank capacity (L)	290
Consumption (L/h)	72.9 Lt/h al 75% del carico
Running time (h)	9.62 h al 75% del carico
Length (mm)	3200
Width (mm)	1300
Height (mm)	1900
Dry weight (Kg)	3430
Silenced	No
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	AVR