

## GREEN POWER GP22A/YW-C OPEN

Reference: 00260CBM



The GREEN POWER 1500 rpm generators are designed for versatile use, from construction sites to industry, from agriculture to civil protection.

Robust welded steel frames with built-in tank of variable capacity produced by Green Power, engines and alternators supplied by the most important manufacturers in the sector and cutting-edge control units are the elements to ensure generators of excellent quality.

The hoods are made of steel, which allows them to be used in tropical environments. The Green Power covers guarantee maximum accessibility for maintenance and cleaning operations.

Green Power's strong point is the design and implementation within the company, a feature that helps to reduce the time to market of the product and allows any customization.

The image is purely indicative.

### Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	16.8
Continuous power three phase (KW)	15.2
Maximum power three phase (KVA)	21
Continuous power three phase (KVA)	19
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	YANMAR4TNV88
Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	Elettrico
Engine capacity (cm <sup>3</sup> )	2190
Number cylinders	4
Cylinders' position	In line

Cooling	Water
Alternator	LINZ ES13MF-4
Poles	4
Fuel tank capacity (L)	60
Consumption (L/h)	3.7 al 75% del carico
Running time (h)	16.21 al 75% del carico
Length (mm)	1500
Width (mm)	700
Height (mm)	1020
Dry weight (Kg)	440
Silenced	No
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	Compound