



MOSA GE 115 PMSX EAS --- SECOND-HAND ---

Reference: USATO5

Technical Sheet

Phase	Single phase / Three phase
Continuous power single phase (KW)	29.2
Continuous power single phase (KVA)	36.5
Maximum power three phase (KW)	88
Continuous power three phase (KW)	80
Maximum power three phase (KVA)	110
Continuous power three phase (KVA)	100
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 63A 3P+N+T CEE - 1 x 230V 16A 2P+T SCHUKO
Engine	PERKINS 1104C-44TAG2, 4 stroke turbo-aftercooler
Engine rpm (rpm)	1500
Starting system	Electric
Engine capacity (cm ³)	4400
Number cylinders	4
Cooling	Water
Inyección	Direct
Alternator	Sincrono trifase, autoeccitato, autoregolato, senza spazzole
Fuel tank capacity (L)	230
Consumption (L/h)	17.1 at 75% of the load

Running time (h)	13.5 at 75% of the load
Acoustic power	96 dB(A)
Acoustic pressure	71 dB(A) at 7 m
Length (mm)	2740
Width (mm)	1200
Height (mm)	1680
Dry weight (Kg)	1680
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Perkins