



BM2 SALLY 1508M Diesel Pressure Washer

Reference: 01SY01

BM2 SALLY 1508M DIESEL PRESSURE WASHER

The BM2 SALLY 1508M Diesel Pressure Washer represents excellence in the field of industrial cleaning equipment. Equipped with an axial pump with steel pistons, it ensures superior and long-lasting performance. Additionally, the presence of a crankshaft pump with ceramic pistons and brass head ensures optimal resistance even in the most extreme conditions.

The Total stop diretto and Total Stop Ritardato TSD system of the BM2 SALLY 1508M allows precise and intuitive control of the machine, ensuring efficient and safe use in any situation. The possibility of having independent pump and burner motor offers unparalleled flexibility, allowing to adapt the pressure washer's performance to specific cleaning needs.

The high-efficiency boiler with double spiral coil of the BM2 SALLY 1508M Pressure Washer ensures rapid and uniform heating of water, enabling to tackle even the most challenging cleaning operations with ease. The presence of motor thermal protection ensures operator safety and machine durability even in the most intense usage conditions.

With cutting-edge design features such as the pump-boiler ignition/switch-off switch and the water temperature regulation thermostat, the BM2 SALLY 1508M offers an unparalleled user experience. The front pivot wheel with brake ensure optimal maneuverability on any surface, while the reinforced metal base ensures the stability and robustness necessary for prolonged use.

The impact-resistant plastic tank and the predisposition for hose reel testify to the attention to detail and versatility of this extraordinary machine.

With cutting-edge technical specifications, including a power supply of 230V-1ph-50Hz, diesel fuel, a maximum pressure of 150 bar - 15 MPa - 2180 psi, and a maximum flow rate of 480 Lt./h, the BM2 SALLY 1508M confirms itself as the ideal choice for those seeking high performance and reliability in any situation.

With a length of 850 mm, a width of 475 mm, and a height of 855 mm, this BM2 SALLY 1508M is compact and maneuverable, yet robust and resistant, with a weight of 70 Kg. It is the perfect solution for a wide range of industrial and commercial applications, ensuring excellent performance and impeccable results in every situation.

Technical Specifications BM2 SALLY 1508M PRESSURE WASHER:

Power supply: 230V-1ph-50Hz
Fuel: Diesel
Frequency: 50 Hz
Voltage: 230 V
Maximum pressure: 150 bar - 15 MPa - 2180 psi
Maximum flow rate: 480 Lt./h
Pump: Axial
Pump rotation: 2800 rpm
Maximum power consumption: 2.6 KW
Maximum temperature: 65 °C
Shut-off system: TS
Diesel tank: 20 l
Length: 850 mm
Width: 475 mm
Height: 855 mm
Weight: 70 Kg.

Are you looking for a dehumidifier with different features? [HERE](#) you can find the entire BM2 range or other specialised brands.

Non-binding images and technical data.

Technical Sheet

Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Pump type	AXIAL
Maximum output capacity (Lt/min)	480
Pressure (bars)	150
Tank capacity (L)	20
Transportability	Wheels and handles
Length (mm)	850
Width (mm)	475
Height (mm)	855
maximum water temperature (°C)	65
Weight (Kg)	70
Maximum input power (KW)	2.6
Pump rotation (rpm)	2800
Maximum pressure (bar-MPa-psi)	150 - 15 - 2180
Stop system	TS