



TF50 LIGHTING TOWER 4x1000W HALOGEN

Reference: TF50 TORRE FARO

TF50 TORRE FARO LIGHT STANDARD 4x1000W ALO

The STANDARD columns are produced starting from a \varnothing of 115 mm with heights ranging from 2.7 m up to 11 m with 4.5, 6, 7 extensions.

These columns are ideal for mounting on medium/large vehicles with various types of headlamps. We offer a wide range of internal spiral cables, especially for 4,5,6 extension columns.

Telescopic pneumatic column in grey anodized aluminium standard MANUALLY STANDARD REVOLUTIONS \varnothing 115 mm 5 extensions complete with anti-rotation pads on each extension, handwheel for manual rotation of the column and internal spiral cable:

- Maximum height of the extension column: 9223 mm
- Minimum height of closed column: 2216 mm
- Maximum sustainable load of the column with centre weight: 40 kg
- Maximum SURVIVOR resistance to wind: 90 Km/h with surface 0,3 m²
- Inner spiral cable: 8 x 1.0 + 4 x 0.5mm² or equivalent
- Column weight: 37,4 Kg CIRCA
- Last section \varnothing : 51 mm

Mechanical micro-switch for signalling of the extended column.

Bracket for external fixing UPPER columns \varnothing 115 mm to the wall.

Bracket for external LOWER fixing (base) of \varnothing 115 mm columns to the wall.

SPECIAL long stroke hand pump complete with safety vent valve and oversized PVC handle.

2m hose for column pump connection.

2x Brackets for fixing the pump to the wall by hand.

Head holder 4x1000W ALOGENI 230V IP65 cod. FL.34125 complete of bracket with headlights mounted for pointing, wired.

Weight: 14Kg

Exposed area: 0.35m²

The image is purely indicative.

Technical Sheet

Phase

Single phase

Frequency (Hz)	50
Voltage (V)	230
Protection degree	IP65
Main body material	Aluminium
Type of lamps	Halogen
Lamps	4 x 1000 W
Telescopic pole	Aluminum
Total lumens (Lm)	88000
Lifting System	Manual lifting system
Maximum height (m)	9
Mast rotation	360°
Height closed (mm)	2216
With generator / Without generator	Without generator
Transportability	Stationary
Stability to wind (Km/h)	90
Outer diameter (mm)	115
Weight (Kg)	59