

DIESEL Water cooled



WFM KING KG160.2IV.tl.SS AUTOMATIC SILENCED GEN

Reference: KG160.2IV.tl

WFM KING KG160.2IV.tl.SS AUTOMATIC SILENT ELECTRONIC GROUP

KING SIZE SERIES SOUNDPROOF VERSION

STANDARD GENERATOR SET EQUIPMENT

- Steel base
- Vibration dampers
- Integrated tank with liquid collection tank
- Industrial silencer for open version
- Battery
- AUTOMATIC SWITCHBOARD ACP 6120 AMF
- Engine with original tropicalized radiator
- Emergency stop button
- Galvanized steel soundproofing cabin with residential muffler

AUTOMATIC SWITCHBOARD ACP 6120 AMF

ELECTRICAL PANEL MOUNTED ON THE GENERATOR SET WITHOUT REMOTE CONTROL

Equipment: electronic control board, circuit breaker, battery charger, square key.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	141
Continuous power three phase (KW)	128
Maximum power three phase (KVA)	176
Continuous power three phase (KVA)	160
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400

Sockets configuration	Terminal box
Emissions Regulations	Stage 3A
Engine rpm (rpm)	1500
Starting system	Electric
Engine capacity (cm ³)	6
Number cylinders	6
Cylinders' position	In line
Cooling	Water
Inyección	Direct
Alternator	Mecc Alte
Poles	4
Three-phase power (KW)	128
Three-phase power (KVA)	160
Efficiency (%)	93.5
Protection degree	IP21
Bore x stroke (mm)	104 x 132
Fuel tank capacity (L)	200
Consumption (L/h)	24,8 @ 80%
Running time (h)	8
Length (mm)	3000
Width (mm)	1130
Height (mm)	1850
Dry weight (Kg)	2350
Silenced	Yes
Brushes	No
PMG	No
Product type	Generator
Type of alternator	Constant Speed
Voltage regulator	AVR
Engine manufacturer	FPT Iveco