



AGROWATT AWT 4-15X PTO Generator Single Phase/ Three Phase 14.8 kVA Compound

Reference: 159753

- For outdoor applications (field and home), in case of blackouts and in areas not served by the power grid
- Supplied with multiplier kit and protection, support with 3-point attachment (patented design), electrical panel with multifunction digital display for real-time data reading (voltmeter, frequency meter, ammeter, hour meter)
- Durability over time and maximum protection (thermal-magnetic and differential)
- Warranty 24 months
- Easy packaging and subsequent storage

Control Panel with:

- 1 CEE 400V (3P+N+E) 32A
- 1 CEE 230V (2P+E) 16A
- 4 pole magnetothermic switch + earth leakage breaker (Id=0.03A) + 2 pole magnetothermic switch + IP65 cover
- voltmeter + frequencymeter + ammeter + hour counter (digital measurement instrument)

Non-binding images and technical data.

Technical Sheet

| Phase | Single phase / Three phase |
|----------------------------------|---|
| Maximum power single phase (KVA) | 5.9 |
| Maximum power three phase (KVA) | 14.8 |
| Frequency (Hz) | 50 |
| Voltage (V) | 230 / 400 |
| Sockets configuration | 1 x 400V 32A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V SCHUKO |
| Engine rpm (rpm) | 1500 |
| Poles | 4 |
| Protection degree | IP44 |
| PTO speed (round/min) | 430 |
| Minimum tractor output (HP) | 45 |
| Transmission ratio | 1 : 7 |

| | |
|-------------------|----------|
| Length (mm) | 1135 |
| Width (mm) | 640 |
| Height (mm) | 915 |
| Dry weight (Kg) | 149 |
| Brushes | Yes |
| Voltage regulator | Compound |
