



## EMILSPRAYER 440 Tank for sanitizers

Reference: EMILSPRAYER 440

### EMILSPRAYER 440 sanitizer tank

EMILSPRAYER 440 sanitizer tank perfect for spraying pesticides for agriculture and products for sanitizing and sanitizing. The EMILSPRAYER 440 sanitizer tank has a capacity of 440 litres with a flow rate of 8.3 litres/minute. The EMILSPRAYER 440 tank is small and handy as it weighs only 52 Kg. Easy to transport the EMILSPRAYER 440 hygienizer tank is suitable to be taken where you need it most.

The EMILSPRAYER 440 sanitizer tank is extremely versatile and has a wide range of applications:

- Professional cleaning and disinfection, using detergents, chemicals and germicidal liquids.
- Gardening and agriculture, in greenhouses and nurseries, using phytosanitary products, herbicides and for pest control

The EMILSPRAYER 440 tank is made of a polymer that is resistant to chemicals and UV rays; in addition, the wall thickness and the targeted design prevent deformation of the product over time and in use. The EMILSPRAYER 440 tank is equipped with a diaphragm pump with continuous duty cycle and valves made of Viton® resistant to chemicals. The integrated pressure switch activates the pump only during the product delivery phase, reducing wear and increasing efficiency. The lance ensures precise delivery by acting on the adjustable nozzle, which allows you to spray a single jet or atomise the product.

The main technical features of the EMILSPRAYER 440 tank are:

- Capacity: 440 litres
- Dimensions: 1200x800xh785 mm
- Weight: 52 Kg
- Electric diaphragm pump 12V, flow rate 8,3 litres/minute, max pressure 4,8 bar
- Continuous duty cycle, Honeywell MICRO SWITCH™ pressure switch
- Santoprene™ membrane and Viton® valves resistant to chemicals
- 4.5 meters of pipe
- Aluminium dispensing lance with gun. Range 9m horizontally + 6m vertically
- Electrical cable and pliers for connection to the power battery and switch
- Lid included.

Images and technical data not binding.

### Technical Sheet

|                                  |     |
|----------------------------------|-----|
| Maximum output capacity (Lt/min) | 8.3 |
| Pressure (bars)                  | 4.8 |
| Tank capacity (L)                | 440 |

---

|                 |      |
|-----------------|------|
| Length (mm)     | 1200 |
| Width (mm)      | 800  |
| Height (mm)     | 785  |
| Dry weight (Kg) | 52   |
| Product type    | Tank |

---