



EMILSPRAYER 980 Tank for sanitizers

Reference: EMILSPRAYER 980

EMILSPRAYER 980 sanitizer tank

EMILSPRAYER 980 sanitizer tank perfect for spraying pesticides for agriculture and products for sanitizing and sanitizing. The EMILSPRAYER 980 sanitizer tank has a capacity of 980 litres with a flow rate of 8.3 litres/minute. The EMILSPRAYER 980 tank is small and handy as it weighs only 95 Kg. Easy to transport the EMILSPRAYER 980 hygienizer tank is suitable to be taken where you need it most.

The EMILSPRAYER 980 sanitizer tank is extremely versatile and has a wide range of applications:

- Professional cleaning and disinfection, using detergents, chemicals and germicidal liquids.
- Gardening and agriculture, in greenhouses and nurseries, using phytosanitary products, herbicides and for pest control

The EMILSPRAYER 980 tank is made of a polymer that is resistant to chemicals and UV rays; in addition, the wall thickness and the targeted design prevent deformation of the product over time and in use. The EMILSPRAYER 980 tank is equipped with a diaphragm pump with continuous duty cycle and valves made of Viton® resistant to chemicals. The integrated pressure switch activates the pump only during the product delivery phase, reducing wear and increasing efficiency. The lance ensures precise delivery by acting on the adjustable nozzle, which allows you to spray a single jet or atomise the product.

The main technical features of the EMILSPRAYER 980 tank are:

- Capacity: 980 litres
- Dimensions: 995x1830x1000h mm
- Weight: 95 Kg
- Side pockets for lifting by forklift trucks (full load), reinforced with galvanized carbon steel tubulars.
- Eyelet for empty lifting from above
- Upper hatch diameter 220 mm with padlockable screw cap with gasket, vent valve and padlockable safety bar.
- Electric diaphragm pump 12V, flow rate 8.3 l/min, maximum pressure 4.8 bar.
- Continuous duty cycle, Honeywell MICRO SWITCH™ pressure switch.
- Santoprene™ diaphragm and Viton® valves resistant to chemicals.
- 4.5 m hose
- Aluminium dispensing lance with gun. Range 9m horizontally + 6m vertically
- Electrical cable and pliers for connection to the power battery and switch.
- Lid included.

Images and technical data not binding.

| | |
|----------------------------------|------|
| Maximum output capacity (Lt/min) | 8.3 |
| Pressure (bars) | 4.8 |
| Tank capacity (L) | 980 |
| Length (mm) | 995 |
| Width (mm) | 1830 |
| Height (mm) | 1000 |
| Dry weight (Kg) | 95 |
| Product type | Tank |
