

IDROMAR WATERMAKER MC3J



Reference: MC3J

Watermaker Idromar MC3J

Watermaker Idromar MC3J part of the MINI COMPACT series, is an excellent Watermaker with an hourly production of fresh water at 25°C of 180 liters/hour and a daily production at 25°C of 4300 liters/day.

The Idromar MC3J Watermaker is designed with high quality components and simple operation.

With a fresh water production that varies from 65 to 180 lt/h, the Watermaker of the MINI COMPACT series are the Idromar proposal for medium-small boats (from 15 to 25 meters), where an intensive and continuous use is not always necessary. The Watermaker of this range are compact, in decomposable version and share functionality, practicality and homogeneity of materials. One of the main features that the Idromar MC3J Watermaker has in common with those in its range is the use of 316L stainless steel: from small details such as screws, bolts and nuts, the entire frame, the vessels that contain the membranes and the high pressure pump head are made of stainless steel to eliminate the phenomenon of corrosion.

The Idromar MC3J Watermaker provides a practical and reliable source of fresh water for boaters with high supply requirements. The Idromar MC3J Watermaker offers you absolute water independence for various diversions such as extended voyages, ocean crossings or fishing.

Technical features of the Watermaker Idromar MC3J:

Hourly production at 25°C: 180 Lt/h
Daily production at 25°C: 4300 Lt/day
Produced water salinity: 300/400 PPM
Power consumption: 1.5 KW
Length: 790 mm
Width: 450 mm
Height: 380 mm
Weight: 110 Kg

Hydraulic connections

Sea suction: 1/2"
Caskets suction: 1/2"
Exhaust: 3/8"
Outflow: 3/8"

If you are looking for another Watermaker similar to the Idromar MC3J then we recommend that you browse our entire catalog dedicated to [nautical watermakers](#).

Images and technical data are not binding.

Technical Sheet

Power (W)

Length (mm) 790

Width (mm) 450

Height (mm) 380

Feed Type 230 V

Production for hour at 25°C (Lt/h) 180

Daily production at 25°C (Lt/day) 4300

Salinity of water produced (PPM) 300/400

Capacity (Lt/h) 180

Remote panel Digital

Weight (Kg)