

IDROMAR WATERMAKER MSK13



Reference: MSK13

IDROMAR WATERMAKER MSK13

Watermaker Idromar MSK13, part of the MINI COMPACT series, is an excellent Watermaker with an hourly production of fresh water at 25°C of 130 liters/hour and a daily production at 25°C of 3100 liters/day.

The Watermaker Idromar MSK13 is designed with high quality components with a simple operation. With a fresh water production that varies from 65 to 180 lt/h, the Watermaker of the MINI COMPACT series are the Idromar proposal for medium-small boats (from 15 to 25 meters), where an intensive and continuous use is not always necessary.

The Watermaker of this range are compact, in a decomposable version, and share functionality, practicality and homogeneity of materials. One of the main features that the Idromar MSK13 Watermaker has in common with those in its range is the use of 316L stainless steel: from small details such as screws, bolts and nuts, the entire frame, the vessels that contain the membranes and the high pressure pump head are all made of stainless steel to eliminate the phenomenon of corrosion.

The Idromar MSK13 Watermaker provides a practical and reliable source of fresh water for boaters with high supply requirements. The Idromar MSK13 Watermaker offers you absolute water independence for various diversions such as extended voyages, ocean crossings or fishing.

The Idromar MSK13 Watermaker systems are small and efficient able to fit into the tightest of spaces due to their complete decomposability.

Technical characteristics of the Watermaker Idromar MSK13:

Hourly production at 25°C: 130 Lt/h
Daily production at 25°C: 3100 Lt/day
Produced water salinity: 300/400 PPM
Power consumption: 1.5 KW
Length: 500 mm
Width: 340 mm
Height: 480 mm
Weight: 95 Kg

Hydraulic connections

Sea suction: 1/2"
Caskets suction: 1/2"
Exhaust: 3/8"
Outflow: 3/8"

If you are looking for another watermaker similar to the Idromar MSK13 then we recommend that you browse our entire catalog dedicated to [nautical watermakers](#).

Images and technical data are not binding.

Vestibulum a sagittis erat. Vivamus sit amet tellus mauris. Morbi efficitur, felis ut tristique consetetur, leo orci gravida neque, vel lacinia mi ex vitae magna. Quisque at pretium justo, in venenatis nulla. Nunc porta dolor quis dui euismod ullamcorper. Nam blandit dui vulputate vehicula varius. Donec in tortor interdum, euismod odio et, mattis mi. Sed scelerisque tellus gravida lacus rutrum faucibus. Mauris ullamcorper urna quis ullamcorper venenatis. Morbi in metus nunc. Proin ornare vel risus et rutrum.

""

Technical Sheet

Power (W)	1500
Length (mm)	500
Width (mm)	340
Height (mm)	480
Feed Type	230 V
Production for hour at 25°C (Lt/h)	130
Daily production at 25°C (Lt/day)	3100
Salinity of water produced (PPM)	300/400
Capacity (Lt/h)	130
Remote panel	Digital
Weight (Kg)	95