



CGM DS4000 SINGLE-PHASE GENERATOR 4KVA

Reference: CGM DS4000

CGM DS4000 single-phase 4 KVA super-silenced generator

CGM DS4000 single-phase 4 KVA generator set with Kohler engine powered by STAGE V diesel at 3000 rpm, compact and easy to use, equipped with enclosure that lowers noise emissions and makes it **supersilenced**.

The CGM DS4000 generator is composed of a Made in Italy alternator from Linz or NSM, self-excited without brushes and with **AVR** voltage regulator.

The CGM DS4000 is equipped with electric start with 12V battery and with a low fuel consumption, in fact it consumes only 1 liter/hour at 75% of the load. This CGM DS4000 genset is perfect for outdoor use.

The CGM DS4000 genset is part of the QUIET series and are characterized by lower fuel consumption and a longer life expectancy than the gasoline-powered range and equipped with soundproof cabin suitable for installation and outdoor use, and increased fuel tank.

The CGM DS4000 3000 rpm is suitable for emergency use only. It is not recommended to be used for more than 6 hours continuously and for more than 500 hours per year.

Technical characteristics of CGM DS4000:

Phase type: Single phase
Maximum power: 3.9 KW
Continuous power: 3.6 KW
Maximum power: 4.4 KVA
Continuous power: 4 KVA
Fuel: Diesel
Voltage: 230 V
Frequency: 50 Hz
Motor: KOHLER KD15-350
Engine speed: 3000 rpm
Starting: Electric
Voltage regulator system: AVR
Consumption: 1 Lt/h at 75% of the load
Tank capacity: 30 Lt
Autonomy: 30 h at 75% load
Length: 1100 mm
Width: 650 mm
Height: 900 mm
Weight: 160 Kg
Supersilenced

Discover the full range reserved for [generator](#) of CGM or other top brands by browsing our catalog to find the one that best suits your needs.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.9
Continuous power single phase (KW)	3.6
Maximum power single phase (KVA)	4.4
Continuous power single phase (KVA)	4
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 230V 16A 3P CEE - 2 x 230V SCHUKO
Engine	Kohler KD 15-350
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm ³)	349
Number cylinders	1
Alternator	Made in Italy
Poles	2
Fuel tank capacity (L)	30
Consumption (L/h)	1
Running time (h)	30
Length (mm)	1100
Width (mm)	650
Height (mm)	900
Dry weight (Kg)	160
Silenced	Yes

Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Kohler
