



GENERATOR RENTAL 40KVA MOSA GE40VSX

Reference: GE40VSX NOLEGGIO

GENERATOR RENTAL 40KVA SET MOSA GE40VSX AVR

Generator Rental 40KVA set MOSA GE40VSX single-phase / three-phase generator, equipped with a VM MOTORI SUN 3105 TE2 diesel engine capable of delivering a maximum power of 40KVA, complete with AVR voltage regulator.

The Generator 40KVA MOSA GE40VSX generator set is equipped with electric or automatic start-up through ATS panel, which allows automatic start-up in case of blackout.

The Generator 40KVA MOSA GE40VSX is compact and convenient to maneuver and transport thanks to its compact size, with a weight of 935 kg in addition to the practical pierceable base.

RENTAL SERVICE

The rental of a generator set has never been so easy: choose the product you want to rent and [FILL OUT THE FORM](#).

Our specialized staff will answer you immediately with the most suitable offer for you!

The equipment available for rental can be shipped throughout Italy and is always ready for action: our team of technicians will always keep it in perfect working condition.

It is advisable to book in advance for the rental of large quantities of machines: this is especially important in conjunction with trade fairs or events, where many people will use the rental service.

The MOSA GE40VSX generator set with a 68-litre tank has a fuel consumption of 7.15 litres/hour at 75% load for an autonomy of more than 9 hours. The alternator is synchronous, self-excited, self-regulated, brushless with class H insulation with AVR voltage regulator.

Voltage Regulator AVR

The MOSA GE40VSX generator set is equipped with a voltage regulator. The AVR is a device that allows you to **keep the output more constant and less dependent on the load**. Thanks to this card there are fewer drops or spikes in current and this makes it safer to use the various devices connected, improving performance and durability.

TECHNICAL FEATURES MOSA GE40VSX

Phase Type: Singlephase / Threephase
Continuous Singlephase output: 13.5 KVA / 10.8 KW
Maximum Singlephase output: 15 KVA / 12 KW
Continuous Threephase output: 36 KVA / 28.8 KW

Maximum Threephase output: 40 KVA / 32 KW
Power Factor cos fi?: 0.8
VAC voltage: 230 / 400 V
Frequency (Hz): 50
Voltage regulator: AVR
Starting frame: Manual / Automatic
Motor: VM MOTORI SUN 3105 TE2
RPM: 1500
Power supply: Diesel
Tank capacity: 68 l
Consumption: 7.15 l/h @ 75 % of load
Autonomy: 9.5 h @ 75 % of load
Acoustic pressure: 66 @ 7m
Length: 1940 mm
Width: 850 mm
Height: 1080 mm
Net weight: 935 Kg

Are you looking to rental a generator set with different technical characteristics? [Here](#) you can find our entire rental fleet in which you can find the perfect generator for you.

Available for Turin and all of Italy.

The images are purely indicative.

neque, a condimentum erat ornare eu. Duis fringilla rutrum eros, eget venenatis ante. Curabitur facilisis, urna blandit lobortis condimentum, est sem ornare arcu, nec convallis odio diam a enim. Etiam scelerisque erat sit amet blandit euismod. Donec vel velit eget ipsum aliquet tempus facilisis et sem. Proin vestibulum finibus imperdiet. Nulla bibendum pellentesque lobortis. Suspendisse potenti. Interdum et malesuada fames ac ante ipsum primis in faucibus. Maecenas ipsum leo, laoreet non quam vel, placerat rhoncus turpis.

...

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	15
Continuous power single phase (KW)	10.8
Maximum power single phase (KVA)	12
Continuous power single phase (KVA)	13.8
Maximum power three phase (KW)	32
Continuous power three phase (KW)	28.8
Maximum power three phase (KVA)	40
Continuous power three phase (KVA)	36
Fuel	Diesel
Frequency (Hz)	50

Voltage (V)	230 / 400
Sockets configuration	1 x 400V 63A 3P+N+T CEE - 1 x 230V 16A 2P+T SCHUKO
Engine	VM MOTORI SUN 3105 TE2, 4 stroke turbocharged
Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	
Engine capacity (cm ³)	2987
Number cylinders	3
Cooling	Air
Inyección	Direct
Alternator	Sincrono trifase, autoeccitato, autoregolato, senza spazzole
Fuel tank capacity (L)	68
Consumption (L/h)	7.1 at 75% of the load
Running time (h)	9.5 at 75% of the load
Acoustic power	91 dB(A)
Acoustic pressure	66 dB(A) at 7 m
Length (mm)	1940
Width (mm)	850
Height (mm)	1080
Dry weight (Kg)	935
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR+Compound
Engine manufacturer	VM MOTORI