



LARIUS THOR K20702 PISTON PAINTER

Reference: K20702

LARIUS THOR K20702 AIRLESS PAINTER

LARIUS THOR K20702 is a high-pressure motorized airless sprayer powered by a 2.8KW petrol engine, which delivers a maximum flow rate of up to 7.5 l/m.

The LARIUS THOR high-pressure airless electric sprayer is equipped with an exclusive electrical control system that safeguards the motor and the circuit board in the event of a lack of grounding, power surges, overheating and inadequate electrical extensions.

LARIUS THOR K20702 is able to apply in total efficiency in the aspiration and in the application of dense and viscous products, in addition thanks to the airless technology the drying times are considerably reduced, this allows the less contribution of diluting liquids to the product.

Thanks to LARIUS THOR K20702, the coating process will be faster and less costly; in fact, it makes it possible to cover the entire application area with fewer passes.

LARIUS THOR K20702 is complete with an electronic device to regulate and control the material outlet pressure of the pump. This device is activated by turning off the motor when it reaches the set threshold, and reactivates it when the value decreases. Thanks to a safety valve the intro process takes place in the maximum reliability and safety, avoiding pressure fluctuation.

TECHNICAL FEATURES LARIUS THOR K20702

Single-phase motor-generator power supply: 9 Kw with asynchronous motor
Power supply: Gasoline
Motor power: 2.8 kW
Max working pressure: 230 bar
Max flow rate: 7.5 L/min
Material outlet: M16 x 1.5 (M)
Sound pressure level: ? 60dB(A)
Guns supplied: 1 L 91X Gun
Nozzle size: Up to 0.051" 1 Gun
Nozzle Size: Up to 0.027" 2 Guns
Width: 720 mm
Maximum Length: 750 mm
Height: 1100 mm
Dry Weight 76 Kg

Are you looking for a painter with different technical features? [Here](#) you can find the full range of LARIUS and other brands specializing in this field.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Phase	Single phase
Voltage (V)	230
Maximum output capacity (Lt/min)	