

DOMETIC FRESHAIR HDE12V

Reference: 8881200126



DOMETIC FRESHAIR HDE12V AIR CONDITIONERS VEHICLES

DOMETIC FRESHAIR HDE12V is a roof air conditioner ideal for agricultural and industrial vehicles with driver cabs, such as cranes and forklifts. Its powerful energy-saving inverter technology ensures fast refrigeration.

The working environment sometimes gets very hot, and it is necessary to keep calm in the cab. With high temperatures and humidity, the driver's concentration and readiness quickly decreases, which is a great safety risk. Thanks to DOMETIC FRESHAIR HDE12V these risks are minimized. The innovative systems are specially designed to meet the special requirements of tractors, cranes, forklifts, forestry and agricultural vehicles and ensure a fast and reliable fresh breeze and efficient cab cooling.

All DOMETIC FRESHAIR HDE12V models are quiet and vibration-free, extremely compact and equipped with inverter technology to save batteries. Their lightweight construction does not significantly load the roof and does not change the vehicle's center of gravity. Thanks to the factory pre-filling with refrigerant, the installation of the air conditioners is quick and easy. DOMETIC FRESHAIR HDE roof air conditioners are available in a total of four different versions suitable for almost all special vehicles: 12V, 24V, 48V and even the 80 volt version can be integrated into almost all electrical systems in the vehicle. The purely electric compressor provides, depending on the model, a large cooling capacity from 2200 W (12 V) up to 3300 W (48 and 80 volts).

TECHNICAL FEATURES DOMETIC FRESHAIR HDE12V AIR CONDITIONERS

Voltage: 12V
Input Current: 90 A
Minimum generator current: 100 A
Cooling power: 2200 W
Compressor: Electric
Inverter technology: YES
Air flow rate: 400 m²/h
Refrigerant: R-134a
Cabin size: 2 - 3 m³
Depth: 766 mm
Width: 537 mm
Height: 213 mm
Weight: 33kg

Are you looking for a product with different characteristics? [HERE](#) you can find the entire DOMETIC range and other specialized brands.

Images and technical data are not binding and subject to change by the manufacturer.

Technical Sheet

Voltage (V)	12
Current (A)	90
Refrigerating yield	2200W
Air flow (m ³ /h)	400
Length (mm)	766
Width (mm)	537
Height (mm)	213
Compressor	Electric
Weight (Kg)	33