

DOMETIC PERFECTCHARGE MCA1235

Reference: 9600000030



DOMETIC PERFECTCHARGE MCA1235 BATTERY CHARGER

DOMETIC PERFECTCHARGE MCA1235 can charge three batteries at the same time and can be used worldwide with an input voltage range from 110 to 230V. Ideal for the regular traveller around the world.

DOMETIC PERFECTCHARGE chargers provide 100% full charge. The unit should be fully charged at least once a month - there is no better way to take care of the batteries and prolong their life. Insufficient charging, on the other hand, can lead to sulfation and consequently premature aging of the battery.

DOMETIC PERFECTCHARGE MCA1235 has three outputs that allow you to charge three battery packs at the same time. Charging is done very gently thanks to state-of-the-art 6-step technology. The DOMETIC PERFECTCHARGE MCA1235 has a compact and lightweight design with practical screw connections for quick and trouble-free assembly. With an input voltage from 110 to 230 V, it can be used everywhere in the world, reliably charging even if the input voltage drops. DOMETIC PERFECTCHARGE MCA1235 is ideal for frequent travelers around the world. Useful improvements: remote control, battery sensor, temperature sensor or battery controller Dometic MPC 01 for up to 30% faster recharging.

DOMETIC PERFECTCHARGE MCA1235 BATTERY CHARGER TECHNICAL FEATURES

Depth: 274 mm
Height: 63 mm
Width: 179 mm
Weight: 1.9kg
Input voltage (direct current): 110/230 V
Output current: 35.00 A
Input Frequency: 50/60 Hz
Battery Type: Lead, AGM, Gel
IP Class: IP20
Energy efficiency: ?87 %
Continuous power at 25: °C 520.00 W
Min. operating temperature: -20.00 °C
Max working temperature: 50.00 °C

Are you looking for a product with different characteristics? [HERE](#) you can find the entire DOMETIC range and other specialized brands.

Images and technical data are not binding and subject to change by the manufacturer.

...

Technical Sheet

| | |
|-------------------|------------------|
| Frequency (Hz) | 50 / 60 |
| Battery type | Piombo, AGM, Gel |
| Length (mm) | 283 |
| Width (mm) | 179 |
| Height (mm) | 63 |
| Input voltage (V) | 110 / 230 |
| Product type | Battery Charger |
| Weight (Kg) | 1.6 |