

## DOMETIC PERFECTCHARGE MCA2440

Reference: 9600000035



### DOMETIC PERFECTCHARGE MCA2440 BATTERY CHARGER

DOMETIC PERFECTCHARGE MCA2440 can charge three batteries at the same time and can be used worldwide thanks to an input voltage range from 110 to 230V. Ideal for frequent travelers around the world.

DOMETIC PERFECTCHARGE chargers guarantee 100% full charging. The battery should be fully charged at least once a month - there is no better way to take care of the Units and extend their life. Insufficient charging, on the other hand, can lead to sulfation and consequently premature aging of the battery.

DOMETIC PERFECTCHARGE MCA2440 has three outputs that allow you to charge three batteries at the same time. Charging is done very gently thanks to state-of-the-art 6-step technology. DOMETIC PERFECTCHARGE MCA2440 has a lightweight and compact design and practical screw connections allow for quick and easy mounting. With an input voltage range from 110 to 230 V, it can be used anywhere in the world and can be charged very efficiently even if the input voltage drops. Ideal for frequent travelers around the world. Useful improvements: Remote control, Hella sensor, temperature sensor or Compatible with the Dometic MPC 01 energy controller for perfect energy management. DOMETIC PERFECTCHARGE MCA2440 comes with bus interface for seamless integration into existing bus systems.

#### TECHNICAL FEATURES DOMETIC PERFECTCHARGE MCA2440 BATTERY CHARGERS

Depth: 303 mm  
Height: 75 mm  
Width: 208.5 mm  
Weight: 3.9kg  
Input voltage (direct current): 110/230 V  
Output current: 40.00 A  
Input Frequency: 50/60 Hz  
Battery Type: Lead, AGM, Gel  
IP Class: IP20  
Energy efficiency: ?87 %  
Continuous power at 25: °C 735.00 W  
Min. operating temperature: -20.00 °C  
Max working temperature: 50.00 °C

#### TECHNICAL FEATURES DOMETIC PERFECTCHARGE MCA2440 BATTERY CHARGERS

Depth: 303 mm  
Height: 75 mm  
Width: 208.5 mm  
Weight: 3.9kg  
Input voltage (direct current): 110/230 V

Output current: 40.00 A  
Input Frequency: 50/60 Hz  
Battery Type: Lead, AGM, Gel  
IP Class: IP20  
Energy efficiency: ?87 %  
Continuous power at 25: °C 735.00 W  
Min. operating temperature: -20.00 °C  
Max working temperature: 50.00 °C

Are you looking for a product with different characteristics? [HERE](#) you can find the entire DOMETIC range and other specialized brands.

Images and technical data are not binding and subject to change by the manufacturer.

\*\*\*

## Technical Sheet

Frequency (Hz)	50 / 60
Battery type	Piombo, AGM, Gel
Length (mm)	283
Width (mm)	179
Height (mm)	63
Input voltage (V)	110 / 230
Product type	Battery Charger
Weight (Kg)	1.6