



## MARELLIMOTORI ALTERNATOR 20KVA MXB-E 160 LA4

Reference: MXB-E 160 LA4

### MARELLIMOTORI MXB-E 160LA4 ALTERNATOR 20KVA THREE-PHASE AVR

MARELLIMOTORI MXB-E 160LA4 is a **Alternator** with a power of 20KVA 8KW, this unit has a self-exciting and self-regulating Brushless operation.

The MXB-E 160LA4 is designed to operate at frequency 50 or 60 HZ, the possibility to work on these two frequencies makes it possible to apply it for any service voltage increasing its versatility, for correct operation. For correct operation it is only necessary to check that the voltage regulator settings are correct for the intended use.

MXB-E 160LA4 can be equipped with a wide range of accessories to meet the customer's needs.

The MarelliMotori Alternator is supplied with 12 terminals (7 terminals), with which it is normally possible to connect both the series and parallel star alternator. According to the needs you can switch from one connection to another, keeping in mind that you must necessarily check the connection of the AVR.

MXB-E 160LA4 threephase can be used as single-phase as required. MarelliMotori MXB-E 160LA4 is a 20KVA alternator equipped with AVR type M00FA122A - MARK VX, suitable for synchronous generators of MARELLIMOTORI construction. The regulator is suitable for operation on both three-phase generators and single-phase generators, allowing a fast, precise and reliable setup.

The M00FA122A is an electronic board designed by MarelliMotori, it is protected by a polyurethane resin that preserves the device from humidity, dust, aggressive environments; the voltage regulator serves to make the current stable, thus avoiding damaging the equipment connected to it, especially electronic equipment such as computers or smartphones. This AVR can be inserted in such a way as to automatically adjust the voltage and possibly also the frequency and / or electrical current according to the set values.

The AVR designed by MarelliMotori is internally equipped with a radio noise filter, which allows to contain radio noise emitted by MarelliMotori generators within the limits set by the European regulations for industrial environments

The AVR is equipped with an internal protection fuse (5 A, 500 V), which intervenes in case of regulator failures or very high overloads in the excitation circuit.

Select the alternator that matches the **technical specifications you require**, visit our [dedicated section](#) to understand how.

#### TECHNICAL FEATURES OF THE ALTERNATOR 20KVA THREEPHASE MXB-E 160LA4

Phase type: Threephase  
Maximum power 50Hz: 20.0 KVA  
Maximum power 50Hz: 16.0 KW  
Maximum power 60Hz: 25.0 KVA  
Maximum power 60Hz: 20. 0 KW

Frequency: 50 - 60Hz  
Voltage: 400V / 480V  
Protection degree: IP23  
A alternator revolutions: 1500 / 1800 rpm  
Number of poles: 4  
Yield: 84.7%  
Weight: 116.0Kg  
Constant speed alternator  
Voltage regulator: AVR

Are you looking for a product with different characteristics? [HERE](#) you can find the entire range **MARELLIMOTORI** and other specialized brands.

Images and technical data not binding and subject to change by the manufacturer

## Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	16
Maximum power three phase (KVA)	20
Frequency (Hz)	50 / 60
Voltage (V)	400
Engine rpm (rpm)	1500
Poles	4
Efficiency (%)	84.7
Protection degree	IP23
Brushes	No
Type of alternator	Constant Speed
Voltage regulator	AVR
Weight (Kg)	102