Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

HELVI AUTOMATIC 30

Reference: 99000066

HELVI AUTOMATIC30 Battery charger

HELVI AUTOMATIC30 is an automatic charger ideal for AGM, GEL and lead batteries. The HELVI AUTOMATIC30 has an electronic charge current control and luminous indicators for charging status. In addition to this it is also equipped with charge current control via potentiometer and automatic charging and maintenance function.
The HELVI AUTOMATIC30 is perfect for charging batteries with a 12 V or 24 V voltage and a charging current of 20 A.
The HELVI AUTOMATIC30 battery charger can charge batteries for various types of vehicles such as motorbikes, cars, vans and boats. The main applications of the HELVI AUTOMATIC30 battery charger are in the automotive and household sector. HELVI AUTOMATIC30 is ideal for batteries of various types such as AGM, GEL and lead-acid batteries.
HELVI AUTOMATIC30 is a single-phase battery charger with 230 V power supply and 50/60 Hz frequency. HELVI AUTOMATIC30 has a rated power of 720 W for a maximum current of 30 A.
The nominal charging capacity of the HELVI AUTOMATIC30 charger is 300 Ah and has infinite charging positions.
HELVI AUTOMATIC30 is very compact and very light thanks to its weight of about 10 Kg equipped with a carrying handle.

Technical characteristics of the HELVI AUTOMATIC30 battery charger:
Phase type: Single-phase
Voltage: 230 V
Frequency: 50/60 Hz
Power: 720 W
Battery voltage: 12/24 V
Maximum current: 30 A
Charging current: 20 A
Charging capacity: 300 Ah 15h
Charging positions: ?
Length: 235 mm
Width: 220 mm
Height: 335 mm
Weight: 10.1 Kg

If you are looking for another product similar to the HELVI AUTOMATIC30 portable charger, then we recommend that you take a look at the entire range dedicated to battery chargers.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Frequency (Hz)	50 / 60

Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

Voltage (V)	230
Power (W)	720
Adjustment positions	?
Nominal current (A)	20
Charge capacity (Ah)	300
Battery voltage (V)	12 / 24
Charging voltage (V)	12 / 24
Current max (A)	30
Length (mm)	235
Width (mm)	220
Height (mm)	335
Product type	Battery Charger
Weight (Kg)	10.1