



MARELLIMOTORI ALTERNATOR 350KVA MJB 315 SB4

Reference: MJB 315 SB4 SAE1 d14

MARELLIMOTORI MJB 315SB4 ALTERNATOR 350KVA THREEPHASE

MARELLIMOTORI MJB 315SB4 is a three-phase alternator capable of delivering a power of **350KVA 280KW**, comes complete with AVR.

The frame of the alternator designed by MarelliMotori is equipped with side ribs to increase the resistance in addition the construction is made of strong welded steel

The 350KVA alternators MarelliMotori for continuous operation are designed to meet the vibration levels according to the standards, therefore they have a spheroidal cast iron or grey cast iron shielding.

The shaft of the MJB 315SB4 is made of carbon steel and obtained by rolling. The shaft is obtained by forging from 290 mm diameter and is tested at the manufacturer in order to verify the absence of defects.

The stator/motor core of MarelliMotors is laminated and enamelled on both sides to minimize eddy current losses

The rotor of MJB 315SB4 is of salient pole type, made with class H flat copper wire insulated with enamel coating.

The winding is held by high quality steel through-bars.

All MarelliMotori are equipped with a large damping cage and are suitable for parallel operation with other generators, if equipped with the parallelization unit.

All MarelliMotori can be designed to meet specific reactance values ($x'd$ and $x''d$).

The MarelliMotori alternators are all equipped with a voltage regulator, in the case of the analog MJB 315SB4. For the correct supply of voltage MARELLIMOTORI 350KVA has the need of an electronic control system, known as "voltage regulator" or "AVR" (acronym of Automatic Voltage Regulator). It guarantees the proper functioning of the machine and above all of the electrical network behind it.

The AVR is an electronic device that converts alternating current with frequency and voltage variable over time into direct current and thus avoids current surges.

The AVR designed by MarelliMotori is internally equipped with a radio noise filter, which allows to contain radio noise emitted by MarelliMotori generators within the limits set by the European regulations for industrial environments

Select the alternator that reflects the **technical specifications you require**, visit our [dedicated section](#) to understand how.

TECHNICAL FEATURES OF THE THREEPHASE 350KVA ALTERNATOR MJB 315SB4

Phase type: Threephase

Maximum power 50Hz: 350KVA

Maximum power 50Hz: 280KW

Maximum power 60Hz: 425KVA

Maximum power 60Hz: 350KW
Frequency: 50 - 60Hz
Voltage: 400V / 480V
Protection degree: IP23
A alternator speed: 1500 / 2250 rpm
Number of poles: 4
Yield: 95.2%
Weight: 920.0Kg
Constant speed
AVR

Are you looking for a product with different characteristics? [HERE](#) you can find the entire range **MARELLIMOTORI** and other specialized brands.

Images and technical data not binding and subject to change by the manufacturer

Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	280
Maximum power three phase (KVA)	350
Frequency (Hz)	50 / 60
Voltage (V)	400
Engine rpm (rpm)	1500
Poles	4
Efficiency (%)	95.2
Protection degree	IP23
Brushes	No
Type of alternator	Constant Speed
Voltage regulator	AVR
Weight (Kg)	920