



HELVI AUTOSTAR 1001

Reference: 99010038

HELVI AUTOSTAR1001 Battery charger

HELVI AUTOSTAR1001 is a battery charger with portable starter equipped with selector and ammeter to adjust and display the charge current level. HELVI AUTOSTAR1001 is protected with internal fuse against short circuits or polarity reversal and thermostatic protection against prolonged starts. HELVI AUTOSTAR1001 is equipped with C.P.S. (car protection system) able to activate and deactivate the start function (boost) totally automatically, to protect the electronics on board the vehicle.

The HELVI AUTOSTAR1001 battery charger is perfect for charging batteries with a 12 V or 24 V voltage and a 60 A current.

The HELVI AUTOSTAR1001 battery charger can charge batteries for various types of vehicles such as cars, vans, boats and tractors. The main applications of the HELVI AUTOSTAR1001 battery charger are in the automotive, construction and agricultural sectors.

HELVI AUTOSTAR1001 is a single-phase/three-phase battery charger with 230/400 V power supply and 50/60 Hz frequency. The HELVI AUTOSTAR1001 battery charger has a rated power of 2200 W for a maximum current of 90 A.

The nominal charging capacity of the HELVI AUTOSTAR1001 charger is 900 Ah and has 14 charging positions plus Boost.

HELVI AUTOSTAR1001 is very compact and comfortable to transport thanks to its wheels despite its weight of about 53 kg.

Technical characteristics of the HELVI AUTOSTAR1001 battery charger:

Phase Type: Single/Triphase

Voltage: 230/400 V

Frequency: 50/60 Hz

Power: 2200 W

Battery voltage: 12/24 V

Maximum current: 90 A

Charging current: 60 A

Maximum surge current: 1000 Acc

Charging capacity: 900 Ah 15h

Charging positions: 14 + Boost

Length: 330 mm

Width: 575 mm

Height: 770 mm

Weight: 53.7 Kg

If you are looking for another product similar to the HELVI AUTOSTAR1001 portable charger, then we recommend that you take a look at the entire range dedicated to battery chargers.

Images and technical data are not binding.

Technical Sheet

Phase

Single phase / Three phase

Frequency (Hz)	50 / 60
Voltage (V)	230 / 400
Power (W)	2200
Adjustment positions	14 + Boost
Nominal current (A)	60
Charge capacity (Ah)	900
Battery voltage (V)	12 / 24
Charging voltage (V)	12 / 24
Current max (A)	90
Length (mm)	330
Width (mm)	575
Height (mm)	770
Product type	Battery Charger
Weight (Kg)	53.7