



GENMAC CLICK RG3000HO GENERATOR 2,9KVA

Reference:

GENMAC CLICK RG3000HO GENERATOR 2,9KVA

The generator Genmac Click RG3000HO single phase has a Honda gasoline powered engine capable of delivering a power of 2,9KVA with the possibility of connection to optional AVR.

The Genmac Click RG3000HO single phase generator is equipped with a Honda engine powered by gasoline with a tank capacity of 3.1 liters for an autonomy of about three and a half hours, complete with manual recoil starter.

The generator is very light and makes it very easy to move for other uses, in addition for an even easier and more dynamic portability is possible the optional supply of a practical transport kit dedicated to this line of generators.

The Genmac 2,9KVA generator is portable of professional quality and you can ask for the supply with optional AVR included.

Optional AVR regulator

The AVR brings a significant improvement in output voltage stability; this is particularly useful with commonly used machines with reactive load, such as refrigerators, freezers, air conditioners and garden machines. This will increase the life of your devices.

The optional AVR is a device that keeps the out voltage more constant and less load-dependent. Thanks to this technology there are fewer drops or current peaks and this makes it safer to use the various devices connected, improving their performance and durability.

Technical features of generator 2,9KVA Genmac Click RG3000HO

Power: Gasoline
Voltage regulator: AVR
Single phase
Continuous output: 2.8KW
Continuous output: 2.8KVA
Maximum output: 2,6KW
Maximum output: 2,9KVA
Voltage: 230V
Frequency: 50Hz
3000 rpm
Tank: 3.1 Lt.
Autonomy @ 75%: 3.5 h fixed revolutions
Starting: Manual
Length (mm): 620
Width (mm): 430
Height (mm): 430

Dry weight (Kg): 36

If you are looking for another product then you can consult on our catalog other [terrestrial gene-groups](#).

Images and technical data are not binding and may be subject to review

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	2.6
Continuous power single phase (KW)	2.2
Maximum power single phase (KVA)	2.9
Continuous power single phase (KVA)	2.4
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Engine	4 Tempi
Engine rpm (rpm)	3000
Starting system	Pull starter
Cooling	Air
Fuel tank capacity (L)	4
Running time (h)	3.5
Length (mm)	620
Width (mm)	430
Dry weight (Kg)	36
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	AVR (optional)