



GENMAC Combiplus RG10000HEO-E5 GENERATOR 12,3KVA

Reference:

GENMAC Combiplus RG10000HEO-E5 GENERATOR 12,3KVA

The **generator Genmac Combiplus RG10000HEO-E5** single phase has a Honda gasoline powered engine capable of delivering a power of 12,3KVA with the possibility of connection to optional AVR.

The GENMAC Combiplus RG10000HEO-E5 generator is equipped with a Honda Stage V engine certified for mobile use in the EU, but which does not comply with others criteria of the regulation. The engine is powered by gasoline by means of a tank with a capacity of 19 liters for an autonomy of about three and a half hours, complete with electric starter.

The Genmac 12,3KVA generator is equipped with a front control panel for portable units, with manual start and oil level sensor, with the possibility of modification by the customer with the optional remote control panel.

In combination with the generator it is possible to request the handling kit specifically designed for the selected model, for a more comfortable transport before the installation on the working lug.

The 12,3KVA generator is equipped with capacitor voltage regulator, on request it is possible to supply it with AVR voltage regulator.

Optional AVR regulator

The AVR brings a significant improvement in output voltage stability; this is particularly useful with commonly used machines with reactive load, such as refrigerators, freezers, air conditioners and garden machines. This will increase the life of your devices.

The optional AVR is a device that keeps the out voltage more constant and less load-dependent. Thanks to this technology there are fewer drops or current peaks and this makes it safer to use the various devices connected, improving their performance and durability.

Technical features of generator 12,3KVA Genmac Combiplus RG10000HEO-E5

Power supply: Gasoline
Firing: Electric
Phase type: Single-phase
Continuous output: 10,4KVA / 9,4KW
Maximum output: 12,3KVA / 11,1KW
Motor: Honda GX630
Emissions regulation: Non-emissioned
Voltage: 230V
Frequency: 50 Hz
3000 rpm
Tank: 19 Lt.

Autonomy @ 75%: 3.8 h fixed rpm
Boosting: Manual
Length (mm): 840
Width (mm): 620
Height (mm): 690
Dry weight (Kg): 159

If you are looking for another product then you can consult on our catalog other [terrestrial gene-groups](#).

Images and technical data are not binding and may be subject to review

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	11.1
Continuous power single phase (KW)	9.4
Maximum power single phase (KVA)	12.3
Continuous power single phase (KVA)	10.4
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Engine	Honda GX630, 4 stroke
Engine rpm (rpm)	3000
Starting system	Elettrico
Cooling	Air
Fuel tank capacity (L)	19
Running time (h)	3.8
Length (mm)	870
Width (mm)	620
Height (mm)	690
Dry weight (Kg)	159
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	AVR (optional)