



GENMAC Combiplus G12000HEO-E5 GENERATOR 13,9KVA

Reference:

GENMAC Combiplus G12000HEO-E5 GENERATOR 13,9KVA

The **generator Genmac Combiplus G12000HEO-E5** single phase has a Honda gasoline powered engine capable of delivering a power of 13,9KVA with the possibility of connection to optional AVR.

The GENMAC Combiplus G12000HEO-E5 generator is equipped with a Honda Stage V engine certified for mobile use in the EU, but which does not comply with others criteria of the regulation. The engine is powered by gasoline by means of a tank with a capacity of 19 liters for an autonomy of about three and a half hours, complete with electric starter.

The Genmac 13,9KVA generator is equipped with a front control panel for portable units, with manual start and oil level sensor, with the possibility of modification by the customer with the optional remote control panel.

In combination with the generator it is possible to request the handling kit specifically designed for the selected model, for a more comfortable transport before the installation on the working lug.

The 13,9KVA generator is equipped with compound voltage regulator, on request it is possible to supply it with AVR voltage regulator.

Optional AVR regulator

The AVR brings a significant improvement in output voltage stability; this is particularly useful with commonly used machines with reactive load, such as refrigerators, freezers, air conditioners and garden machines. This will increase the life of your devices.

The optional AVR is a device that keeps the out voltage more constant and less load-dependent. Thanks to this technology there are fewer drops or current peaks and this makes it safer to use the various devices connected, improving their performance and durability.

Technical features of generator 13,9KVA Genmac Combiplus G12000HEO-E5

Power Supply: Gasoline
Firing: Electric
Phase Type: SinglePhase / ThreePhase
SinglePhase Continuous output: 3.9 KVA / 3.5 KW
Maximum SinglePhase output: 4.6 KVA / 4.2 KW
ThreePhase Continuous output: 11.8KVA / 9.4KW
ThreePhase Maximum output: 13.9KVA / 11.1KW
Motor: Honda GX630
Socket panel: 1 x 16A 230V - 1 x 32 A 400 V
Voltage: 230 / 400V
Frequency: 50 Hz

3000 rpm
 Tank: 19 Lt.
 Autonomy @ 75%: 3,8 h fixed revolutions
 Starting: Manual
 Length (mm): 870
 Width (mm): 620
 Height (mm): 690
 Dry weight (Kg): 157

If you are looking for another product then you can consult on [our catalog](#) other [terrestrial generator](#).

Images and technical data are not binding and may be subject to review

Technical Sheet

| Phase | Single phase / Three phase |
|-------------------------------------|----------------------------|
| Maximum power single phase (KW) | 4.2 |
| Continuous power single phase (KW) | 3.5 |
| Maximum power single phase (KVA) | 4.6 |
| Continuous power single phase (KVA) | 3.9 |
| Maximum power three phase (KW) | 11.1 |
| Continuous power three phase (KW) | 9.4 |
| Maximum power three phase (KVA) | 13.9 |
| Continuous power three phase (KVA) | 11.8 |
| Fuel | Gasoline |
| Frequency (Hz) | 50 |
| Voltage (V) | 230 / 400 |
| Engine | HONDA GC160 |
| Engine rpm (rpm) | 3000 |
| Starting system | Elettrico |
| Cooling | Air |
| Fuel tank capacity (L) | 19 |
| Running time (h) | 3.8 |
| Length (mm) | 870 |
| Width (mm) | 620 |
| Height (mm) | 690 |
| Dry weight (Kg) | 157 |
| Product type | Generator |
| ATS Switch device | Optional ATS |

Voltage regulator

AVR (optional)