



GENMAC Combipro G5500HC-M5 GENERATOR 5,8KVA

Reference:

GENMAC COMBIPRO G5500HC-M5 SINGLE-PHASE GENERATOR 5,8KVA

The generator Genmac Combipro G5500HC-M5 three phase is equipped with a Honda gasoline powered engine capable of delivering a power of 5,8KVA with capacitor voltage regulator (AVR optional).

The Generators of the **Genmac Combipro G5500 series** are among the most **silent** in their category, thanks to the side closing panels and the oversized muffler. The panels are covered with a **silent** silent material in polyester, this material is recyclable, washable, class 1, fire retardant and self-extinguishing.

These power generators are built with a **compact and robust** structure with sturdy **wheels and handle** integrated into the frame, which makes them handy and easily transportable. The 300mm diameter wheels with double reinforcement, with which Combipro generators are equipped, are integrated in the structure and the retractable handle can be folded to avoid unnecessary hindrance when not in use. On the frontal part there is also a full length support to avoid sinking into the ground.

The Genmac Combipro mounts a **Honda OHV 4-stroke petrol engine**. They are very reliable engines that guarantee efficient combustion and **low fuel consumption**. The engines with 5,8KVA generators are also equipped with a protection system that causes the **engine to stop if the oil level is too low**.

The Genmac 5,8KVA Generator is equipped with **electronically controlled injection engines** of the GX series.

The 5,8KVA generator with capacitor voltage regulator, on request it can be supplied with AVR.

AVR Voltage Regulator

All models in the Genmac Combipro series are available with optional AVR voltage regulator. The AVR is a device that allows to **maintain the output more constant and less load-dependent**. Thanks to this card you have fewer drops or current peaks and this makes it safer to use the various devices connected, improving their performance and durability.

The model equipped with AVR card is highly recommended, as it guarantees a significant improvement in the stability of the output voltage; this feature makes the generators particularly suitable with common use machines with reactive load such as refrigerators, freezers, air conditioners and garden machines. Thanks to the AVR you can enjoy greater stability and thus increase the life of your devices.

TECHNICAL FEATURES OF GENERATOR GENMAC COMBIPRO G5500HC-M5

Voltage regulator : capacitor (AVR Optional)
Power supply: Gasoline
Firing: Manual
Phase type: Singlephase / Threephase
Singlephase continuous output: 1.7KVA / 1.5KW

Maximum singlephase output: 2KVA / 1.8KW
 Threephase continuous output: 5.0KVA / 4.0KW
 Threephase maximum output: 5.8KVA / 4.6KW
 Motor: Honda GX270
 Receptacle panel: 1 x schuko 230V - 1 x 16A 230V - 1 x 16A 400 V
 Emission standard: Stage V
 Voltage: 230 / 400V
 Frequency: 50 Hz
 3000 rpm
 Tank: 25 Lt.
 Autonomy @ 75%: 15 h fixed rpm
 Boosting: Manual
 Length (mm): 800
 Width (mm): 640
 Height (mm): 700
 Dry weight (Kg): 99

If you are looking for another product then you can see on [our catalog](#) other generator

Images and technical data not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	1.8
Continuous power single phase (KW)	1.5
Maximum power single phase (KVA)	2
Continuous power single phase (KVA)	1.7
Maximum power three phase (KW)	4.6
Continuous power three phase (KW)	4
Maximum power three phase (KVA)	5.8
Continuous power three phase (KVA)	5
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 16A 3P+N+T CEE - 1 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO
Engine	HONDA GX270
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Manual recoil

Cooling	Air
Poles	2
Fuel tank capacity (L)	25
Running time (h)	
Acoustic pressure	69 dB(A) at 7 m
Length (mm)	
Width (mm)	
Height (mm)	700
Dry weight (Kg)	
Silenced	Yes
Super silenced	No
ATS Switch device	No ATS
Voltage regulator	AVR (optional)
Engine manufacturer	Honda