

## EGM RP8000SE GENERATOR 7KW

Reference: RP8000-SE



### EGM RP8000-SE SINGLEPHASE GENERATOR 7KW

The generator EGM RP8000-SE singlephase is equipped with a gasoline engine capable of delivering 7KW power with optional AVR voltage regulator.

The RP8000-SE singlephase EGM generator provides reliable power for home, work and leisure environments Safe powering of home appliances and other electronic devices Outdoor party solution.

The 7KW singlephase generator is equipped with bolted, heavy duty wheels and hinged handle make it a robust and easy to transport. The recessed sockets with snap-on safety covers make it more secure.

The generator has a practical double-curved handle, which can be folded down for easy mobility and storage. EGM RP8000-SE has an all-steel construction and a large metal tank with fill indicator. The generator guarantees an efficient and silent operation thanks to the OHV engine that allows to deliver a maximum power of 7KW.

The AVR is indispensable to make the generator work at its best, it all needs an electronic control system, an AVR, which guarantees the good functioning of the machine and of the electrical network behind it.

#### TECHNICAL CHARACTERISTICS OF THE SINGLEPHASE GENERATOR EGM RP8000-SE 7KW

Phase Type: Single-phase  
Single-phase Continuous Power: 6.5 KVA / 6.5 KW  
Single-phase Maximum Power: 7 KVA / 7 KW  
VAC Voltage: 230 V  
Frequency (Hz): 50  
Voltage Regulator: AVR  
Starter Panel: Manual recoil  
RPM: 3000  
Power Supply: Gasoline  
Tank Capacity: 25 l  
Consumption: 11.5 l/h @ 50 % of load  
Autonomy: 2.17 h @ 50 % of load  
Sound pressure: 97 dB(A) @ 7m  
Length: 700 mm  
Width: 526 mm  
Height: 580 mm  
Net weight: 95 Kg

If you are looking for another product then you can consult other terrestrial generators in [our catalog](#).

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	7
Continuous power single phase (KW)	6.5
Maximum power single phase (KVA)	7
Continuous power single phase (KVA)	6.5
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 x 230V 16A 2P+T CE
Emissions Regulations	Stationary Use
Engine rpm (rpm)	3000
Speed governor	Mechanical
Starting system	Manual recoil
Cooling	Air
Poles	2
Fuel tank capacity (L)	25
Consumption (L/h)	11.5 l/h @ 50 %
Running time (h)	2.17 h @ 50 %
Acoustic pressure	97 dB(A) @ 7m
Length (mm)	700
Width (mm)	526
Height (mm)	580
Dry weight (Kg)	95
Silenced	No
Super silenced	No
ATS Switch device	No ATS
Voltage regulator	AVR