

PARKER ULTROCLEAR DF UC1200-215 DESALINATOR 189 LT/H

Reference: ULTROCLEAR DF UC1200-215



PARKER ULTROCLEAR DF UC1200-215 DESALINATOR 189LT/H

The desalinator PARKER ULTROCLEAR DF UC1200-215 is a reverse osmosis plant in compact or modular configuration with 189lt/h flow rate.

Parker UltroClear DF converts seawater to double purified. Its reliable piping connection enables a direct feed that activates automatic operation and produces pure water when fed directly into the system.

The ultrapure water is 99% solids-free. Perfect for rinsing hulls, windows and extending the life of your marine equipment. Gently lifts debris and dries without stains.

The Parker desalinator with 189lt/h flow rate is a reverse osmosis system that adopts an easy principle whereby the molecules of a solvent, such as liquid, pass from a concentrated solution to a less concentrated solution with a pressure on the more concentrated solution higher than the osmotic pressure. Each reverse osmosis system is equipped with a semi-permeable membrane that can separate the solute from the solvent in order to obtain a pure liquid and discard the solute.

The Parker Ultroclear desalinator is able to retain all impurities and dissolved mineral salts by delivering fully osmotized water.

The membranes are the true core of this type of systems. The membranes of the desalinator differ according to their size, normally expressed in inches, and the delivery capacity, expressed in GPD. The membranes that make up Ultroclear therefore, are 1200 GPD 189lt/h.

Thanks to its small size, it can be applied in boats or particularly narrow and unwieldy premises, maintaining optimal performance in all circumstances.

TECHNICAL CHARACTERISTICS ULTROCLEAR PARKER DISSALATOR DF UC1200-215 189lt/h

Production: 189lt/g

Daily production: 4536lt/g

Nominal performance: +-15% at 820 PSI / 57 bar, 77°F / 25°C and 35,000 PPM TDS

Salt rejection: Minimum 99.2%, average 99.4%

Water produced temperature: Room temperature

Pressure adjustment: User adjustable (manual)

Salinity monitoring: The system's salinity monitoring components give a continuous TDS reading in ppm

Salinity range: Designed to use seawater up to 50,000 PPM TDS

Temperature range Max: 122°F / 50°C, Min. 33°F / .5°C

Power supply flow: 4.5 gpm / 17 lpm

Reverse Osmosis Membrane: Selected high rejection/high performance tri-polyamide aromatic membrane, thin film composite, spiral wound, single pass.

Chlorine tolerance: 0.1 PPM

pH Range: 3-11

Supply Pressure: Maximum 35 psi / 2.41 bar / 2.46 Kg/cm²

Width: 531mm

Length: 719 mm

Height: 336 mm

Weight: 20kg

If you are looking for another desalinator we suggest you to browse our entire catalog dedicated to [nautical desalinators](#).

Images and technical data are not binding.

Technical Sheet

Length (mm)	531
Width (mm)	719
Height (mm)	336
Dry weight (Kg)	20
Production for hour at 25°C (Lt/h)	189
Daily production at 25°C (Lt/day)	4536