Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

CGM OK 4-320L

Reference: CGM OK 4-320L /

CGM OK4-320L 4 X 320W

CGM OK4-320L is a light tower with diesel generator, hydraulic lifting equipped with 4 floodlights capable of delivering a light output of 320W each.

CGM OK4-320L is equipped with KOHLER KDW702 diesel engine, 1500 rpm with liquid cooling capable of delivering a mechanical power of 6.6 Hp.

CGM OK4-320L is equipped with a galvanized steel lifting tower capable of extending up to 8.5 meters in maximum height, including 4 stabilization feet to secure the light tower once opened. The lifting tower is electrically operated and by a hydraulic system that allows maximum extension without effort.

CGM OK4-320L is equipped with LINZ ELECTRIC alternator which increases the effectiveness of the KOHLER engine thanks to its integrated voltage regulator, allowing high efficiency with low consumption. The fact tower has a 140Lt capacity tank, which allows the continuous operation of the CGM for 280 hours.

CGM OK4-320L TECHNICAL FEATURES

Floodlights: 4 LED 320W
Illuminated Area: 5000 Mq
Max Height: 8.5 Mt
Lift: Hydraulic motorized
Telescopic pole: Galvanized steel
Wind Stability: nr 4 stabilizers
Guides for forklift forks: n.8
Lumen per luminaire: 41550 lm
Continuous electric power: 3.5 KVA
Rotation: 359 degrees
Power outlet: 230V (max 1,8kVA)
Voltage: 230V
Frequency: 50Hz
Number of turns: 1500 turns/mn
Engine: KOHLER KDW702
Starting type: Electric battery
Tank capacity: 140 Lt
Autonomy with working lights: 280 hr
Engine power: 6.6 Hp / 4.9 KW
N. Cylinders: 2 in line
Suction: Aspirated
Cooling: Water

Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

Alternator: LINZ ELECTRIC
Type: Brushless
No. of Poles: 4
Width: 1200 mm
Length: 1130 mm
Height Closed: 2450 mm
Height Opened: 8500 mm
Dry weight: 810 Kg
Voltage regulation: Condenser

Looking for a light tower with different features? Here you can find the full range CGM or other specialized brands.

Images and technical data are not binding and may be subject to revision by the supplier.

Technical Sheet

Phase	Single phase
Continuous power single phase (KVA)	3.5
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 230V
Engine	KOHLER KDW702
Engine rpm (rpm)	1500
Starting system	Electric
Number cylinders	2
Cylinders' position	In line
Cooling	Water
Alternator	Linz
Poles	4
Tank capacity (L)	140
Type of lamps	LED
Lamps	4 x 320W
Telescopic pole	Galvanized steel
Illuminated area (m^2)	5000
Lifting System	Hydraulic lifting system
Maximum height (m)	8.5
Mast rotation	359°
Open size (mm)	1200 x 1130 x 8500
Closed size (mm)	1200 x 1130 x 2450
Dry weight (Kg)	810