



## CGM PR4-160L

Reference: PR4-160L /

### CGM PR4-160L LED Tower Light

CGM PR4-160L is a simple light tower with manual lifting winch equipped with 4 floodlights capable of delivering a light output of 160W each.

The CGM light tower consists of a trolley with folding handles with safety grips.

CGM PR4-160L is a light tower set up to be combined with a generator of your choice between:

- 6000SP SUPER POWER, with CGM gasoline engine, AVR, 25lt tank
- CX5000 DELUXE with HONDA gasoline engine, AVR, 15lt tank
- DS4000 QUIET with KOHLER diesel engine, AVR, 30lt tank and soundproof enclosure

CGM PR4-160L is equipped with a galvanized steel lifting tower capable of extending up to 5.5 meters maximum height, including 3 feet of stabilization to secure the light tower once opened.

#### CGM PR4-160L TECHNICAL FEATURES

Floodlights: 4 LED 160W  
Illuminated Area: 2200 Mq  
Max Height: 5.5 Mt  
Lift: Manual  
Telescopic pole: galvanized steel  
Wind Stability: nr 3 stabilizers  
Lumen per luminaire: 20350 lm  
Electrical power: 5 KVA / 4.5 KW  
Rotation: 355 degrees  
Towing trolley: Lento  
Forklift guides: nr 2  
Power outlet: 16A 230V  
Voltage: 230V  
Frequency: 50 Hz  
Width: 1300 mm  
Length: 900 mm  
Height Closed: 2160 mm  
Height Opened: 5500 mm  
Dry weight: 280 Kg

You can find many other different light towers in the [section dedicated](#) to lighting systems.

Images are purely indicative

## Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 230V 16A
Type of lamps	LED
Lamps	4 x 160 W
Telescopic pole	Galvanized steel
Illuminated area (m <sup>2</sup> )	2200
Total lumens (Lm)	81400
Lifting System	Manual lifting system
Maximum height (m)	5.5
Mast rotation	355°
Open size (mm)	1300 x 900 x 5500
Closed size (mm)	1300 x 900 x 2160
Transportability	Slow Trailer
Dry weight (Kg)	280