



CGM MR4-75L

Reference: CGM MR4-75L /

CGM MR4-75L 4 X 75W

CGM MR4-75L is a light tower with manual winch lift, equipped with 4 floodlights capable of delivering a luminous power of 75W each.

CGM MR4-75L can be combined with a generator of your choice to best power the floodlights.

CGM MR4-75L features a galvanized steel lifting tower capable of extending up to a maximum height of 5.5 meters. The lifting tower is manually operated through a winch system that allows it to extend up to 5.5m

CGM MR4-75L can be combined with an optional tripod equipped with 4 stabilization feet to allow the tower to be opened with greater wind stability and safety.

Images and technical data are not binding and may be subject to revision by the supplier.

CGM MR4-75L TECHNICAL SPECIFICATIONS

Floodlights: 4 LED 75W
Illuminated Area: 1500 Mq
Max Height: 5,5 Mt
Lift: Manual
Telescopic Pole: Galvanized steel
Wind Stability: nr 4 stabilizers
Lumen per luminaire: 9225 lm
Rotation: 360 degrees
Voltage: 230V
Frequency: 50 Hz
Width: 350 mm
Tripod Width: 2200 mm
Length: 350 mm
Tripod length: 2200 mm
Height Closed: 2050 mm
Height Opened: 5700 mm
Dry Weight: 97 Kg

Are you looking for a product with different characteristics? [Here](#) you can find the full range CGM or other specialized brands.

Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Type of lamps	LED
Lamps	4 x 75W
Telescopic pole	Galvanized steel
Illuminated area (m ²)	1500
Lifting System	Hydraulic lifting system
Maximum height (m)	5.5
Mast rotation	360°
Open size (mm)	350 x 350 x 5700
Closed size (mm)	350 x 350 x 2050
Dry weight (Kg)	97