



CGM BE4-160L BE TOWER

Reference: CGM BE4-160L /

CGM BE TOWER BE4-160L LIGHTER TOWER 160W X 4

CGM BE4-160L is a galvanized steel telescopic light tower equipped with 4 LED projectors each capable of delivering a light output of 160W.

The BE TOWER CGM BE4-160L light tower has an input plug and a 16A 230V output socket for the with which it can be combined with other units.

CGM BE4-160L is designed to be combined with a CGM generator set and can be connected in series in order to use one generator for multiple lighting units.

CGM BE4-160L TECHNICAL SPECIFICATIONS

Floodlights: 4 x 160W Ioduri
Illuminated Area: 3000 @ 5 lux
Max Height: 8.5 Mt
Lift: Hydraulic
Telescopic pole: Telescopic pole in galvanized steel
Wind Stability: nr 4 stabilizers
Lumen per luminaire: 20350 lm
Total lumens: 81400 lm
Rotation: 359 degrees
Forklift guides: nr 8
Power outlet: 16A 3P input plug
Connectable in series: YES
Voltage: 230V
Frequency: 50 Hz
Width: 1200 mm
Length: 1000 mm
Height Opened: 8500 mm
Height Closed: 2300 mm
Dry weight: 550 Kg

Looking for a Light Tower with different characteristics? [Here](#) you can find the whole range of CGM or other specialized brands

Images and technical data are not binding and may be subject to change by the supplier

Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 230V 16A 3P CEE
Type of lamps	LED
Lamps	4 x 160 W
Telescopic pole	Galvanized steel
Illuminated area (m ²)	3000
Total lumens (Lm)	81400
Lifting System	Hydraulic lifting system
Maximum height (m)	8.5
Mast rotation	359°
Open size (mm)	1200 x 1000 x 8500
Closed size (mm)	1200 x 1000 x 2300
Dry weight (Kg)	550