



## HELVI fastDARK WELDING MASK

Reference: 21905116

### HELVI fastDARK WELDING MASK

HELVI fastDARK is a welding mask that offers optimal face protection by giving the possibility of adjustments according to one's needs.

To offer maximum protection HELVI fastDARK gives the user the possibility to adjust:

- **delay time:** you can adjust the time it takes for the filter to become transparent again once the welding is finished. You can choose a time ranging from 0.1 to 1.0 second .
- **sensitivity:** you can adjust the sensitivity to ambient light.  
LO (low) = not very sensitive to light.  
HI (high) = very sensitive to light. This setting is ideal for welding at low currents and for welding in dimly lit environments.  
You can adjust the sensitivity to ambient light.

#### TECHNICAL FEATURES HELVI tigMAKER 210HF Pulse

Optical Class: 1/1/1/2  
Filter Size: 110 x 90 x 9 mm  
Visual: 92 x 42 mm  
Sensors: 2  
Light Level: 4. 0  
Darkening degree: 9-13  
Moling: YES  
Protection adjustment: External. variable degree  
UVIR protection: up to DIN 16  
Light to dark time: 1/25000 s  
Dark to light time: 0. 1 - 1.0 s  
Sensitivity/Delay: Continuously adjustable  
Power supply: Solar cells and 1 CR2032 battery  
ON/OFF: Automatic  
Low battery alarm: Yes, red light  
Minimum Amp/TIG setting: >10A AC - DC

Looking for a Welding Mask with different features? [Here](#) you can find the whole range of HELVI or other specialized brands

Images and technical data are not binding and may be subject to revision by the supplier

## Technical Sheet

Motor insulation class	H
Length (mm)	210
Width (mm)	220
Height (mm)	310
Weight (Kg)	