



MOSA TF KIT I9 L-4x350 Lighting Tower

Reference: C07000G0

MOSA TF KIT I9 L-4x350 Light Tower

MOSA TF I9 L-4x350 is a light tower equipped with 4 halogen lamps 350 W, provides a high illuminated area of over 4800 square meters.

Two features that optimize and facilitate the positioning and transport on mobile vehicles such as trucks, vans or on the special trailer approved for road traffic, available as an option, single or double axle, complete with 4 extendable and foldable stabilizers, lighting system and front wheel.

MOSA TFOSA I9 L-4x350

The MOSA TF I9 L-4x350 light towers are mobile lighting units designed to ensure maximum reliability of operation even in the harshest environments.

One of the most distinguishing features is the upper protection of the telescopic pole, a MOSA exclusive, which safeguards one of the most delicate points of the entire MOSA TF I9 L-4x350 from atmospheric agents, building site slag, dust and leaves.

The pole, with hydraulic lifting of the MOSA TF I9 L-4x350 is complete with safety valve, reaches a maximum height of 9 meters. The different types of lamps available guarantee a great versatility of use in any work environment and for both outdoor and indoor applications.

Sectors of use: construction, rental, events, emergency.

Technical characteristics MOSA TF I9 L-4x350:

- Telescopic galvanized pole
- Hydraulic lifting
- Safety valve for manual descent
- Projectors that can be manually oriented on the two axes
- Base prepared for fixing on frame
- Lifting hooks

Maximum height (mt.): 9

Rise: Hydraulic

Lit area: 4800 m²

Lamps: LED

Lights: 4 x 350 W

Transportability: Fixed

Dry weight (Kg): 410

Min. (mm): 600x1070x1870

Max. (mm): 600x1410x8600

Wind stability (Km/h): 80

Pole rotation: 340°

Are you looking for a light tower with different features? [Here](#) you can find the entire range Mosa or other brands specializing in the field.

The images are purely indicative.

Technical Sheet

Type of lamps	LED
Lamps	4 x 350 W
Telescopic pole	Galvanized
Illuminated area (m ²)	4800
Total lumens (Lm)	22382
Lifting System	Hydraulic lifting system
Maximum height (m)	9
Mast rotation	340°
Open size (mm)	600 x 1410 x 8600
Closed size (mm)	600x1070x1870
Transportability	Stationary
Stability to wind (Km/h)	80 Km/h
Dry weight (Kg)	410
Brushes	No
Feed Type	Single-Phase